



This is an electronic reprint of the original article. This reprint may differ from the original in pagination and typographic detail.

Gómez Millán, Gerardo; Hellsten, Sanna; King, Alistair W.T.; Pokki, Juha-Pekka; Llorca, Jordi; Sixta, Herbert

A comparative study of water-immiscible organic solvents in the production of furfural from xylose and birch hydrolysate

Published in: Journal of Industrial and Engineering Chemistry

DOI: 10.1016/j.jiec.2018.12.037

Published: 25/04/2019

Document Version Peer-reviewed accepted author manuscript, also known as Final accepted manuscript or Post-print

Published under the following license: CC BY-NC-ND

Please cite the original version:

Gómez Millán, G., Hellsten, S., King, A. W. T., Pokki, J.-P., Llorca, J., & Sixta, H. (2019). A comparative study of water-immiscible organic solvents in the production of furfural from xylose and birch hydrolysate. *Journal of Industrial and Engineering Chemistry*, 72, 354-363. https://doi.org/10.1016/j.jiec.2018.12.037

This material is protected by copyright and other intellectual property rights, and duplication or sale of all or part of any of the repository collections is not permitted, except that material may be duplicated by you for your research use or educational purposes in electronic or print form. You must obtain permission for any other use. Electronic or print copies may not be offered, whether for sale or otherwise to anyone who is not an authorised user.

A comparative study of water-immiscible organic solvents in the production of furfural from xylose and birch hydrolysate

Gerardo Gómez Millán†‡, Sanna Hellsten†, Alistair W. T. King§, Juha-Pekka

Pokki^{II}, Jordi Llorca[‡], Herbert Sixta^{*}[†]

†	G. Gómez Millán, DSc. S. Héllsten, Prof. H. Sixta
	Department of Bioproducts and Biosystems
	School of Chemical Engineering
	Aalto University
	Vuorimiehentie 1, 02150 Espoo (Finland)
	*E-mail: herbert.sixta@aalto.fi
I	J. P. Pokki
	Department of Chemical and Metallurgical Engineering
	School of Chemical Engineering
	Aalto University
	PL 16100, 00076 Espoo (Finland)
‡	G. Gómez Millán, Prof. J. Llorca
	Department of Chemical Engineering, Institute of Energy Technologies and Barcelona Research Center in Multiscale Science and Engineering
	Universitat Politècnica de Catalunya
	Eduard Maristany 10-14, 08019 Barcelona (Spain)
§	Alistair William Thomas King
	Materials Chemistry Division, Chemistry Department
	University of Helsinki
	Al Virtasen Aukio 1, Helsinki (Finland)

Abstract

Furfural (FUR) was produced from xylose using a biphasic batch reaction system. Water-immiscible organic solvents such as isophorone, 2-methyltetrahydrofuran (2-MTHF) and cyclopentyl methyl ether (CPME) were used to promptly extract FUR from the aqueous phase in order to avoid the degradation to humins as largely as possible. The effect of time, temperature, organic solvent and organic-to-aqueous ratio on xylose conversion and FUR yield were investigated in auto-catalyzed conditions. Experiments at three temperatures (170, 190 and 210 °C) were carried out in a stirred microwave-assisted batch reactor, which established the optimal conditions for achieving the highest FUR yield. The maximum FUR yields from xylose were 78 mol% when using CPME, 48 mol% using isophorone (due to its phase-behavior nature) and 71 mol% in the case of 2-MTHF at an aqueous to organic phase ratio of 1:1. Birch hydrolysate was also used to show the high furfural yield that can be obtained in the biphasic system under optimized

conditions. The present study suggests that CPME can be used as a green and efficient extraction solvent for the conversion of xylose into furfural without salt addition. **Keywords**: xylose, furfural, prehydrolyzate liquor, 2-MTHF, CPME, isophorone

Introduction

Hemicellulose, one of the three major components in lignocellulosic biomass including cellulose and lignin, is a cross-linked fibrous amorphous heteropolysaccharide, consisting mostly of different pentoses (C_5) with some hexoses and uronic acids sugar monomers [1]. Hemicelluloses are the second most abundant natural polymer [2]. The main C_5 sugars found in hemicellulose are xylose and arabinose. Xylan, which is degraded during kraft pulping of hardwood, is currently valorized to sugar-based products in very small quantities. In these cases, xylan is typically hydrolysed to xylose and then further reduced to xylitol. In a typical hardwood kraft pulping process, about 50% of the xylan in the wood is degraded to carboxylic acids, which are enriched in the black liquor together with the degraded lignin. After thermal concentration to thick liquor, the organic matter is burnt an the energy obtained is used for the pulping process [3]. Therefore, valorization of these attractive industrial streams extends the possibility to create new markets and new economic models.

According to the United States Department of Energy, furfural (furan-2-carbaldehyde, FUR) is one of the top 10 most rewarding bio-based platform molecules [4]. FUR is industrially produced by the dehydration of xylose and other C₅-sugars in aqueous solutions usually found in hemicellulosic fractions of lignocellulosic biomass. The FUR application range varies from the chemical industry, where is used as solvent and extracting agent, to the agrochemical sector, where it is employed as nematicide,

fungicide and herbicide; it can also be involved in processes in the pharmaceutical and cosmetic industries [5]. Furthermore, FUR serves as a platform molecule to produce furfuryl alcohol (via hydrogenation) [6,7] with applications in the food industry as flavoring agent, for the synthesis of furan resins and in the biofuel sector. Other important molecules that can be potentially synthesized from FUR are: tetrahydrofurfuryl alcohol, furan as a diene in Diels-Alder reactions, tetrahydrofuran, dihydropyran and furoic acid [8]. Besides, FUR has been identified as a direct or indirect feedstock to more than 80 chemicals [9,10]. Consequently, FUR plays a major role as a platform molecule in future bio-refineries developments [1].

In the commercial process, FUR yield does not exceed 50 mol% and is associated with various environmental problems, such as toxic effluents derived from mineral acids (sulfuric or hydrochloric acid) and high energy demand due to the need of high temperatures of approximately 200 °C. In order to avoid the formation of high salt loads resulting from the neutralization of mineral acid catalysts, the development of easily-separable solid acid catalysts is being undertaken (e.g. zeolites [11-20], sulfonated graphenes [21-24], sulfated zirconia [6,25], alumina [26], coated activated carbon [15,27], among others [1]) and ionic liquids [5]. These recent advances suggest operational improvements involving green principles [28]. However, solid catalysts might face deactivation, fouling or low catalytical activity after the first cycle of reuse. Moreover, the unknown consequences of long-term use of ionic liquids, together with their elevated cost and yet inefficient recovery and recycling, set significant drawbacks to scale up their development [5].

In addition, the limited FUR yields are partly due to the formation of insoluble polymers (humins). These humins are decomposition products of both xylose and FUR, which react via resinification or condensation [1,29-32]. A recent article showed limited FUR yields of 49% in aqueous phase at 210 C in 1 h using a xylose solution of 186 mmol I⁻¹ [33]. Several studies have suggested ways to inhibit the formation of humins and subsequently increase the FUR yield. One approach is to selectively extract the FUR instantaneously from the aqueous solution into an organic phase [34]. Trimble and Dunlop were the pioneers to implement this idea using ethyl acetate as the extracting media [35]. Subsequent research included studies on various organic solvents such as 2-secbutylphenol, 4-n-hexylphenol, 2-methoxy-4-propylphenol [36], 1-butanol [37], yvalerolactone [13,38], cyclohexanol [39], methyl isobutyl ketone (MIBK) [34,39], dimethyl sulfoxide (DMSO) [40,41], 1,3-Dimethyl-2-imidazolidinone (DMI) [42] and widely-used toluene [39]. However, most of these studies involve the addition of salts (used as phase modifiers) due to the high solubility of organic solvents in water, in order to increase the partition coefficient. Hence producing high salt waste after work-up, corrosion of the reactor and possible deactivation of acid sites on solid acid catalysts [43,44]. Besides, several solvents are toxic and are not ideal for industrial application. In contrast, green solvents from renewable sources such as 2-MTHF and CPME [45-47] are commercially available offering sustainable alternatives in order to extract FUR without the addition of salts due to its aqueous-immiscibility nature and provide a superior phase separation at the organic-water interface without forming emulsions [48]. An organic solvent with similar properties, isophorone, has been recently reported, which claims a higher distribution coefficient of FUR at 25 °C in a quaternary mixture of FUR+water+isophorone+acetic acid

(14) [49] than CPME (8.5) and 2-MTHF (8) [50]. Under normal conditions, isophorone has a solubility in water of 1.2 g/ 100 g at 20 °C [49], CPME of 1.1 g/ 100 g at 23 °C [47] and 2-MTHF of 14 g/ 100 g at 20 °C [51].

The aim of this work is to evaluate the production of FUR from xylose using a biphasic system including a novel promising water-immiscible solvent, isophorone, in which FUR is extracted thus increasing the FUR yield by reducing FUR decomposition reactions via condensation and resinification. The performance of isophorone is compared with other known water-immiscible organic solvents like CPME and 2-MTHF. An additional advantage of this system is the prevention of salt addition that offers a greener perspective in the FUR production. Furthermore, a liquid-liquid extraction (LLE) model was developed in order to predict the mass fractions of formed FUR in aqueous and organic phases under experimental conditions.

Experimental

Materials

D-Xylose powder (99%), isophorone, 2-MTHF and CPME were purchased from Sigma Aldrich.

D-Xylose powder was used in the experiments without further purification. Millipore grade water was used for preparing the solutions.

The birch hydrolysate was supplied by Stora Enso (Stora Enso, Imatra, Finland), which was used for the dehydration reaction experiments.

Methods

Xylose Dehydration Reaction Experiments in Biphasic System

Single containing D-xylose solution in a concentration typical for biomass hydrolysate (186 mmol l⁻¹) was freshly prepared before the experiments (Table A1 in the Supporting Information). These experiments can be considered as an auto-catalyzed reaction system where some side products (namely carboxylic acids) or intermediates, formed during the reaction, may have a catalytic effect [52,53]. In a typical experiment, the samples were prepared by heating 3 ml of an aqueous solution of 186 mmol l⁻¹ xylose using a borosilicate glass reactor (V = 10 cm³) with magnetic stirring (600 min⁻¹), an irradiation power of \leq 850 W for maximum 2 min and microwave-assisted heating (Monowave 300, Anton Paar GmbH, Graz, Austria). The prepared solutions were tested for FUR yield, selectivity and xylose conversion at the reaction temperatures of 170, 190 and 210 °C with different reaction by compressed air inside the reactor until it reached 60 °C. The highest temperature and the longest reaction time studied at the present work were 210 °C and 180 min, respectively.

Birch Hydrolysate Dehydration Reaction Experiments in Biphasic System

The birch hydrolysate was filtered by using a glass filter with porosity 4 (Duran). The composition of the liquor was determined according to the analytical method NREL/TP-510-42623 [54]. The concentration of monomeric sugars was measured by high-performance anion exchange chromatography with pulse amperometric detection (HPAEC-PAD) by using a Dionex ICS-3000 column.

Determination of FUR and by-products

Samples for analysis were drawn from both the organic phase (top) and aqueous phase (bottom) after microwave heating. Xylose and FUR from aqueous phase were analyzed separately by High Performance Liquid Chromatography (HPLC) operating a Dionex UltiMate 3000 HPLC (Dionex, Sunnyvale, CA, USA) device equipped with refractive index (RI) and ultraviolet (UV) diode array detectors. Product separation was achieved on a HyperRez XP Carbohydrate Ca⁺ column (Thermo Scientific, Waltham, MA, USA). Aqueous sulfuric acid (0.005 mol I⁻¹) was used as eluent with a flow rate of 0.8 ml min⁻¹. The column temperature and the RI-detector temperature were set to 70 °C and 55 °C, respectively. The FUR and hydroxymethylfurfural (HMF) concentration was determined by the UV-detector at a wavelength of 280 nm. The xylose concentration was analyzed simultaneously by the RI-detector and the UV-detector at 210 nm for a crosscheck [55]. FUR from the organic phase was analyzed by gas chromatography with a flame ionization detector (GC-FID) relative to iso-butanol as internal standard (IS). The column used was a DB-WAXetr (30 m, 0.32 mm i.d., 1 µm film thickness) from Agilent Technologies Inc. The injected samples (0.5 µL) were subjected to a split ratio of 20:1 in the inlet maintained at 250 °C and pressure of 12.967 psi. Helium was used as the carrier gas. The oven was initially maintained at 80 °C for 1 min, after which the temperature was increased to 250 °C at 30 °C min⁻¹. The FID was operated at 250 °C with hydrogen, air, and helium delivered at 30 ml min⁻¹, 380 ml min⁻¹, and 29 ml min⁻¹, respectively.

In this study conversion is defined in terms of moles of reactant converted per unit volume of reactor (eq. 1). Selectivity, at an instant, is the generated amount of moles of desired product referred to the moles of reactant converted (eq. 2). Yield is the amount in moles of desired product, FUR, produced relative to the amount of the key reactant, xylose (eq. 3) [56]. The following equations have been used for the mathematical evaluation of the obtained results:

$$X_{xyl} = \frac{c_{xyl}^{in} - c_{xyl}^{f}}{c_{xyl}^{in}} \times 100 \ [\%]$$
(Eq. 1),

$$S_{xyl}^{fur} = \frac{c_{fur}}{c_{xyl}^{in} - c_{xyl}^{f}} \times 100 \ [\%]$$
 (Eq. 2),

$$Y_{fur} = \frac{c_{fur}}{c_{xyl}} \times 100 \,[\%]$$
 (Eq. 3),

where X, S, Y are the– conversion of xylose, selectivity to FUR and FUR yield, respectively; *c* is the– concentration in mmol (the subscripts to be read as follows: *xyl*, *fur*, *in*, *f* are the– xylose, FUR, initial, final).

Furfural Decomposition Reaction Experiments in Biphasic System.

FUR decomposition reactions were conducted using a 10 ml borosilicate glass reactor with magnetic stirring (600 min⁻¹) and microwave-assisted heating (Monowave 300, Anton Paar GmbH, Graz, Austria). The vials were filled with 1.5 ml of 5 wt% FUR solution and 1.5 ml of the organic solvent. The prepared solutions in the biphasic system were tested for FUR concentration at the reaction temperatures of 170, 190 and 210 °C with different reaction times in the range of 30-180 min. The reaction vial was rapidly cooled down to 60 °C after the reaction via a stream of compressed air that was blown onto the reactor. Samples were stored at 0 °C until analyzed.

Results and Discussion

Furfural partitioning in a Biphasic Reactor System.

The partitioning of FUR in different organic solvents was investigated by conducting hydrothermal reactions wherein a solution of 5 wt% FUR in water was heated with isophorone, 2-MTHF, and CPME for 30 min at 190 °C at five different ratios of aqueous to organic solvent: 1:5, 1:2, 1:1, 2:1 and 5:1 (v/v). Figure 1 shows the FUR partition coefficients (P) obtained with the three organic solvents, where *P* was calculated using eq. 4 [39].

$$P = \frac{[FUR]_{org}}{[FUR]_{aq}}$$
(Eq. 4)

A FUR partition coefficient of 9.1 was obtained with an aqueous to isophorone fraction ratio of 1:5. This value decreased to 7.5, 8.4, 6.9 and 6.6 as the aqueous to isophorone fraction ratio increased to 1:2, 1:1, 2:1 and 5:1, respectively. For 2-MTHF (4.6) and CPME (3.8) lower partition coefficients were obtained compared to isophorone.



Figure 1. Partition coefficients for furfural among isophorone, 2-MTHF and CPME. Partition coefficients were determined for a solution of 5 wt% furfural in water heated for 30 min at 190 °C (and then cooled down to 60 °C) at five different ratios of aqueous to organic solvent: 1:5, 1:2, 1:1, 2:1 and 5:1 (v/v).

In a recent article using isophorone [49], the partition coefficient of FUR in a ternary system was studied (FUR+isophorone+water). It can be observed that when the FUR fraction and temperature increase, the partition coefficient tends to decrease. However, under the experimental conditions of the present paper, the partition coefficient does not vary significantly (low mass fractions of FUR). Even though the partition coefficient of FUR when CPME and 2-MTHF tends to increase, when the FUR fraction and the temperature increase [57], its values do not vary significantly under the presented experimental conditions, due to the low mass fractions of FUR formed.

Furfural Production from Xylose

The effect of xylose dehydration on FUR production was studied in biphasic systems made with isophorone, 2-MTHF or CPME serving as the organic phase and an aqueous xylose solution.

Effect of organic phase and aqueous to organic phase ratio

Solubility of water in the organic solvents has been measured in recent papers for isophorone [49], 2-MTHF and CPME [57]. It is observed that solubility of water in the three organic solvents used in the present paper is minimal under the given experimental conditions.

The effect of different organic solvents and an aqueous solution of 186 mmol I⁻¹ was studied in biphasic systems at 190 °C in 30 min. For this, three water-immiscible solvents were studied: isophorone, 2-MTHF and CPME. Simultaneously, the effect of aqueous-to-organic phase ratio on xylose conversion and FUR production was investigated.

Consequently, five ratios of aqueous to organic phase (1:5, 1:2, 1:1, 2:1, 5:1; v/v) were planned. The FUR yields are shown in Figure 2 and are calculated using equation 3.

Figure 2 shows that the FUR yield increases as the aqueous to organic ratio increases from 1:5 up to 1:1 (v/v), regardless of the organic solvent. At ratios of aqueous to organic volumes of 2:1 to 5:1, we suggest that a higher FUR yield is prevented through the generation of increased decomposition products. The highest FUR yield (14%, Figure 2a) is reached (at 190 °C in 30 min) when employing isophorone in an aqueous to organic phase ratio of 1:1. When 2-MTHF is employed (Figure 2b), the highest FUR yield (13%) is also reached in an aqueous to organic phase ratio of 1:1. When CPME is used (Figure 2c), a FUR yield of 26% is reached at 190 °C in 30 min. Figure A1 (in the Supporting Information) displays the xylose conversion and the FUR selectivity in the three biphasic systems. When employing isophorone, the xylose conversion varied from 36% to 41%. When using 2-MTHF, xylose conversion varied from 40% to 44%; and CPME, where xylose conversion fluctuated from 41% to 56%. Selectivity to FUR inceases as the aqueous to organic ratio increases from 1:5 to 1:1 (v/v), thereafter it decreases when increasing the aqueous to organic phase ratio to 5:1. The decrease of FUR selectivity could be due to saturation of the organic solvent to extract FUR.



Figure 2. Effect of aqueous-to-organic ratio on FUR yield when using isophorone (a), 2-MTHF (b) and CPME (c) as organic phase. The effect was determined for a solution of xylose (186 mmol I^{-1}) heated at 190 °C in 30 min at five different ratios of aqueous to organic solvent: 1:5, 1:2, 1:1, 2:1, 5:1 (v/v). The error bars shown are one standard deviation from duplicate analyses.

Effect of reaction temperature

The influence of the reaction temperature on the dehydration of xylose and the resulting FUR yield was studied by using a 0.186 mol l^{-1} xylose concentration in a twophase mixture at a temperature range between 100 and 200 °C for 30 min (water-organic solvent, 5:1 *v*/*v*) under microwave irradiation (Figure A2 in the Supporting Information). D-xylose is not soluble in the organic phase [49,57,58]. Thereby, the FUR yield varied between 0 and 23 mol% (Fig. A2a). The effect of reaction temperature on FUR yield, xylose conversion and selectivity to FUR when working with an aqueous to organic ratio of 5:1 was further investigated. A low FUR yield was obtained from 100 to 150 °C (approximately 0%). The reason for lower FUR yield at the low reaction temperature was due to incomplete xylose conversion (below 15%, Fig. A2b). The highest FUR yield when employing CPME and 2-MTHF is 23% (at a xylose conversion of 57% and 49%, respectively) in 30 min at 200 °C, and when using isophorone is 18% (at a xylose conversion of 50%) at 200 °C (in 30 min).

Effect of reaction time

The effect of reaction time on the production of FUR was studied by conducting reactions between 30 to 180 min at 170, 190 and 210 °C with isophorone, 2-MTHF and CPME with a xylose solution of 186 mmol l⁻¹. Due to the low vapor pressure of 2-MTHF, reactions using this organic solvent at reaction temperatures of 210 °C were not possible to perform. Figure 3 shows the effect of reaction time when using CPME on FUR yield, xylose conversion and selectivity to FUR. In agreement with previous studies [59], FUR yield and xylose conversion were observed to be strongly influenced by the reaction temperature.

Figure 3 displays the effect of reaction time on FUR yield, xylose conversion and selectivity to FUR at 170, 190 and 210 °C when using CPME as organic solvent in an aqueous to organic phase ratio of 1:1. As seen in Figure 3a, after the first 60 min of the hydrothermal reaction the FUR yield was increased up to four times by increasing the temperature from 170 to 190 °C. The highest FUR yield (78%) was reached at 190 °C in

3 h. The maximum selectivity (Figure 3c) to FUR formation was 93%, 81% and 71% at temperatures of 170, 190 and 210 °C, respectively.

It can be seen, that at times longer than 120 min, the FUR yield obtained at 190 °C surpasses the FUR yield obtained at 210 °C. Under high reaction temperatures (210 °C) we assume that CPME does not extract FUR as efficiently. Therefore FUR tends to stay in the aqueous phase rather than in the organic phase, hence decomposition reactions of FUR occur faster.



Figure 3. Effect of temperature and reaction time on (a) FUR yield, (b) xylose conversion, (c) selectivity to FUR in the dehydration of 28 g l⁻¹ xylose when using CPME as organic solvent with an aqueous to organic phase ratio of 1:1. Lines are to guide the eye.

When isophorone is used as water-immiscible solvent, the results are shown in Figure 4. For the first 60 min of the treatment the FUR yield was increased up to four times by increasing the temperature from 170 to 190 °C when employing isophorone to aqueous fraction ratio of 1:1 (Figure 4a). The highest FUR yield (49%) was reached at 190 °C in 3 h. The maximum selectivity (Figure 4c) to FUR formation was 48%, 54% and 43% at temperatures of 170, 190 and 210 °C, respectively. A similar phenomenon occurred when employing isophorone as observed with CPME. Under high reaction temperatures (210 °C), FUR tends to stay in the aqueous phase rather than in isophorone, hence decomposition of FUR occurs faster. In comparison to the performance of isophorone to 2-MTHF and CPME (Fig. 5), it might be that FUR enters the organic phase but undergoes degradation in the presence of the solubilized water within isophorone. Afterwards FUR precipitates out once a certain molecular weight is reached.



Figure 4. Effect of temperature and reaction time on (a) FUR yield, (b) xylose conversion, (c) selectivity to FUR in the dehydration of 186 mmol I⁻¹ xylose when using isophorone as organic solvent with an aqueous to organic phase ratio of 1:1. Lines are to guide the eye.

Figure 5 shows FUR yield, xylose conversion and selectivity to FUR when employing 2-MTHF. Figure 5a shows that the first 60 min of the treatment the FUR yield was increased up to two times by increasing the temperature from 170 to 190 °C when employing 2-MTHF to aqueous fraction ratio of 1:1. The highest FUR yield (71%) was reached at 190 °C in 3 h. The maximum selectivity (Figure 5c) to FUR formation was 58% and 80% at temperatures of 170 and 190 °C, respectively. Due to the low vapor pressure

of 2-MTHF, reactions using this organic solvent at reaction temperatures of 210 °C were not possible to perform.



Figure 5. Effect of temperature and reaction time on (a) FUR yield, (b) xylose conversion, (c) selectivity to FUR in the dehydration of 186 mmol I⁻¹ xylose when using 2-MTHF as organic solvent with an aqueous to organic phase ratio of 1:1. Lines are to guide the eye.

Recent research of the auto-catalyzed system in aqueous phase has been published under similar experimental conditions [33,60]. The maximum FUR yield (48-49%) was reached at reaction temperatures of 210 °C and 220 °C in 1 h and 35 min, respectively, corresponding to a xylose conversion of 100% and 96%, respectively. It was observed that the FUR yield goes through a maximum and thereafter decreases with increasing reaction time. Decrease of FUR yield is due to the condensation and resinification reactions that take place between FUR and xylose [29,31,32], producing humins, which are detrimental to FUR yield. In contrast, when using pure organic solvent, recent studies have shown low solubility of xylose in CPME [57,61]. Le Guenic et al recently reported [61] a limited selectivity to FUR (2%) after the reaction took place at 170 C in 40 min when using only CPME in monophase.

Furfural decomposition in the biphasic system

To increase understanding of the behavior of FUR under the conditions of microwaveassisted reaction in the presence of an organic solvent, it is essential to know its degradation rate. The FUR degradation experiments were performed for the autocatalyzed reactions using CPME and isophorone at the temperatures of 170, 190 and 210 °C. The experimental data showing the remaining fractions of FUR found in the aqueous and organic phases at various reaction times are presented in Fig. 6a and 6b, when adding isophorone and CPME, respectively. The figures illustrate the effect of the treatment temperature and the usage of 1:1 aqueous to organic phase ratio on the degradation rate of FUR. The results show a clear dependency of FUR degradation on the temperature, similarly to the data presented in earlier reports in monophasic systems [62-64]. It can be seen that when increasing the temperature the FUR degradation increases for both auto-catalyzed with isophorone and CPME. In addition, the results show that FUR is decomposed more rapidly in the presence of isophorone. The highest degree of degradation, 38%, was observed at 210 °C after 180 min. When CPME was employed as organic solvent, the highest degree of degradation was below 12%.



Figure 6. The remaining furfural at various reaction times during auto-catalyzed degradation when employing isophorone (a) and CPME (b) to aqueous phase of 1:1 (v/v). The decomposition of furfural was determined for a solution of 5 wt% furfural (squares – 170 °C, circles – 190 °C, triangle – 210 °C).

In order to confirm FUR decomposition in the presence of isophorone, a temperature level study was performed from 110 °C to 210 °C in 60 min when employing an aqueous to organic phase ratio of 1:1 (v/v). Fig. A3 (in the Supporting Information) shows that FUR decomposes linearly under the experimental conditions reaching the highest degree of degradation (24%) at 210 °C in 60 min.

Liquid-liquid equilibrium study

To get FUR from aqueous phase to organic phase the distribution should favor high solute distribution coefficients of FUR when defined as in Eq. (5)

$$K_i = \frac{w_{i,organic}}{w_{i,aqueous}}$$
(Eq. 5)

where i refers to any component in the mixture. Isophorone-FUR-water data at 30, 50 and 70 °C was recently published by Ershova et al [49] demonstrating that at the equilibrium state the aqueous phase contains around 1 wt% isophorone and around 0.8–3.8 wt% FUR, whereas the organic phase contains 4.5–6.4 wt% water. In contrast, CPME-FUR-water and 2-MTHF-FUR-water at 20, 50 and 70 °C have been recently reported [57]. At the equilibrium state of 2-MTHF-FUR-water the aqueous phase contains 4.8–8.8 wt%. In the case of CPME-FUR-water the aqueous phase contains 4.8–8.8 wt%. In the case of CPME-FUR-water the aqueous phase contains less than 1 wt% CPME and around 1.7–11 wt% FUR, whereas the organic phase contains 0.8–6 wt% water.

In order to confirm the values predicted by the LLE model, one test in each biphasic system was performed at 190 °C in 120 min (black dot). These tests show the consistency of the model in both aqueous and organic phase in the three biphasic systems. Even though when CPME and 2-MTHF are employed, FUR in the aqueous phase is not fully in line with predicted data, the values are comparable to the predicted data. This small devialliation could be due to small droplets of organic solvent in the aqueous sample. Figures 7, 8 and 9 summarize the measured (dots) and predicted (lines) LLE phase equilibrium.



Figure 7. CPME and FUR binary LLE in mass fractions at atmospheric pressure. 70 °C Männisto et al., [50] 120-210 °C lines are extrapolated based on UNIQUAC model, filled symbol and solid line – organic (upper) phase, open symbol and dashed line – aqueous (lower) phase. Left figure shows the aqueous phase enlarged.



Figure 8. Isophorone (IP) and FUR binary LLE in mass fractions at atmospheric pressure. 70 °C symbols from Ershova et al. [49], 120-210 °C lines are extrapolated based on UNIQUAC model, filled symbol and solid line – organic (upper) phase, open symbol and dashed line – aqueous (lower) phase. Left figure shows the aqueous phase enlarged.



Figure 9. 2-MTHF and FUR binary LLE in mass fractions at atmospheric pressure. 70 °C symbols from Männisto et al. [50], 120-210 °C lines are extrapolated based on UNIQUAC model, filled symbol and solid line – organic (upper) phase, open symbol and dashed line – aqueous (lower) phase. Left figure shows the aqueous phase enlarged.

From the Figures 7-9 it can be seen that the slope of tie-line changes from positive to negative as temperature increases. It means that the distribution coefficient of FUR is higher than one close to room temperature but at the reaction temperature of this work it is less than one. The calculated distribution coefficients are presented in Figure 10.



Figure 10. Distribution coefficient K for FUR in raffinate in the system when: a- CPME, bisophorone and c- 2-MTHF are added to the system.

Based only on liquid-liquid equilibria (LLE) 2-MTHF gives K values of FUR higher than one at 150 °C but CPME and isophorone less than one. At 170 °C and higher temperature all solvents give the K-value of FUR less than one. In industrial practice, this could mean that lower temperatures are preferred for the FUR to be extracted adequately by the organic phase.

In the present work from the three water-immiscible organic solvents studied, isophorone shows a higher distribution coefficient of FUR, however CPME demonstrates a higher selectivity towards FUR without decomposition. This suggests that FUR undergoes decomposition reactions, potentially including isophorone as a co-reactant. Alternatively, the rate of degradation of FUR may be increased by an increasing content of water at temperatures approaching 200 °C. These possibilities were investigated by NMR analysis of the degradation of FUR: isophorone molar ratios of 1:1 and 1:10 at 190 °C over 30 min and 120 min (Figures A4-A6 in the Supporting Information). Potential mechanisms for this degradation might be, for example, Diels-Alder cycloaddition (isophorone as hindered dienophile), Aldol condensation (isophorone C6 reacting as nucleophile at the FUR aldehyde) and Michael addition (isophorone C3 as α - β unsaturated electrophile). Other reactivity may of course be possible [65-67].

Despite colourisation of the solutions after heating, ¹H NHMR analysis (in DMSO -d₆ at 27 °C) showed that no new decomposition products were formed in significant quantities (Supporting Information Figures A7 and A8) and no precipitate was visible that might indicate significant condensation of FUR. Presence of water in the organic phase is another potential reason for losses of FUR. However, there is no literature LLE data

available for water and isophorone at the higher temperatures studied. The maximum temperatures quoted in the literature are only up to 70 °C [49]. The changing miscibility of water and isophorone up to 190 °C was crudely assessed by heating a mixture of isophorone (1 ml) and water (1 ml) in sealed narrow bore sample vials from 110 °C to 190 °C, with 5 min equilibration time every 10 °C (Figure A7 in the Supporting Information). At room temperature and even up to 110 °C the mixtures clearly form separate phases. However, as the temperature exceeds 150 °C the organic phase becomes cloudy, indicating dispersion of water into the phase. This phenomenon may be a result of increased hydrate (hemiketal) formation at the elevated temperatures or simply kinetic dispersion of clusters into the organic phase. These explanations, however, are speculative in the absence of accurate LLE data and require further studies to understand this phenomenon.

Further NMR experiments were also carried out after heating equivolume mixtures of FUR:H₂O, FUR:isophorone, FUR:H₂O:isophorone and Xylose:H₂O:isophorone at 210 °C for 3 h. The FUR:H₂O mixtures quickly degraded and formed a dark precipitate, from condensation of the FUR. All other mixtures colourised to some degree but did not form precipitate. The organic phases of each reaction were separated and evaporated to almost complete dryness by heating with a heat-gun (<150 °C) under oil pump vacuum with N₂ trap, to remove the majority of the volatiles (trace water, FUR or isophorone). The residues and also the solids from the FUR:H₂O mixture were added to DMSO-d₆ for NMR analysis. A multiplicity-edited HSQC and HSQC-TOCSY were recorded for the FUR:isophorone residue (Figure A8). This showed resonances characteristic of trace FUR and isophorone, in addition to several other low molecular weight decomposition

products or imputiries. The main visible TOCSY correlations between the main aliphatic region (1-2.5 ppm in ¹H) and the FUR CH region (5.5-10 ppm in ¹H) seem to be between 2-CH and 3Cme or 4-CH₂ on isophorone, or related compounds. Thus, there does not see to be any low molecular weight species that show obvious linkages between FUR and isophorone. However, this is not absolute proof that they do not exist and further inspection of the ¹H spectrum (Figure A9, top) shows that the low molecular weight aldehyde (CHO) functionalities are largely missing indicating potential linkage at the aldehyde functionality on FUR .

When a diffusion-edited ¹H experiment for the same sample is measured, compared to the standard ¹H experiment (Figure A9), it is clear to see that there is polymeric material in the DMSO-d₆ solution. Diffusion-editing has the effect of removal of the low molecular weight resonances and retention of the polymeric resonances [68]. The retained signals in the soluble organic fraction from the FUR: isophorone reaction correspond to both polymerised FUR and isophorone. Unfortunately, relaxation of these polymeric signals are too fast and abundances are too low so that we do not see the correlations to any significant degree, by HSQC or HSQC-TOCSY. Therefore, this makes it unclear if the FUR and isophorone-derived resonances are present due to co-precipitation or covalent linkage between the two moieties. If we compare the ¹H spectrum from the isolated solids from the FUR:H₂O reaction against the diffusion-edited ¹H spectra for the soluble fractions in the FUR:H₂O and FUR:isophorone reactions (Figure A10) it is clear that all mixtures contain polymeric material. In the case of the solids fraction from the FUR:H₂O reaction, the sample only partially dissolved in DMSO-d₆ indicating that there is a much higher molecular weight cross-linked polymer present. However, the spectrum looks very similar

to that of the soluble fraction of the corresponding FUR:H₂O reaction, except for the presence of the H₂O and DMSO peaks (standard ¹H experiment – not diffusion-edited). The diffusion-edited ¹H spectrum for the soluble organic fraction of the FUR:isophorone reaction contains a similar FUR CH region but is missing the aldehyde (CHO), likely attributable to the FUR aldehyde functionality on a polymerised furan backbone. In addition, there is the major contribution of the aliphatics, attributable to isophorone to the polymerised furans. Reaction of isophorone at the aldehyde functionality of FUR is most likely via a Baylis-Hillman or Aldol type reaction. However, some isophorone 2-CH (5.8 ppm) is clearly still present in the polymeric fraction, so a combination of these and other possible mechanisms may be responsible.

When the diffusion-edited ¹H spectra for FUR:isophorone, FUR:H₂O:isophorone and Xylose:H₂O:isophorone are compared (Figure A11) we see some further changes from the inclusion of water with organics. The peak shape of the aliphatics change indicating new mechanisms of polymerisation. Aldehydes, FUR CHs isophorone 2-CH and acetals are missing. However, this may be due to the formation of a rigid enough polymer backbone that the signals relax before the collection phase of the NMR experiments pulse sequence. Alternatively, a Diels-Alder-type or other cycloaddition reactions may be induced, which would lead to formation of aliphatic resonances. Water may have a significant effect here as formation of FUR hemiacetal would increase its reactivity, as a diene towards [4+2] cycloaddition, under the conventional Diels Alder HOMO-LUMO energy ordering. After all, water is well-known to have a rate-enhancing effect on the Diels-Alder reaction [69]. While this NMR result is inconclusive, clearly there is polymer

forming to some degree from polymerisation of FUR and/or isophorone in the presence of water.

While none of these NMR studies give measures of increased degradation of FUR, it shows that:

- 1. water does have a significant effect on the condensation of FUR [31,32]
- isophorone may allow for increased miscibility with water at higher temperatures, which may lead to increased degradation kinetics of FUR
- co-polymerisation of isophorone and FUR is likely occurring, which may lead to increased losses of both FUR and isophorone to some degree. This may be highly temperature dependent

Clearly more in-depth studies are required to isolate suitable polymeric fractions that might allow for more detailed NMR studies, to trace spin-systems between FUR and isophorone moieties, and to avoid the effects of transverse relaxation (T_2) which reduces the quantity of the diffusion-edited ¹H experiment.

Furfural production from birch hydrolysate

The production of FUR from birch hydrolysate was studied under optimized conditions for the dehydration of C_5 sugars (190 °C, 1:1 aqueous to CPME phase ratio, under microwave irradiation). The initial composition of the birch hydrolysate is given in Table A1 (in the Supporting Information).

The FUR yield increased from 37 mol% to 68% with an increasing time from 30 to 90 min at 190 °C when employing an aqueous to CPME phase ratio of 1:1 (Figure 11). The highest mole fraction of hydroxymethylfurfural (HMF) was 0.01 mmol (Figure A12 in the Supporting Information), which is in agreement with previous studies when using birch hydrolysate to produce FUR from pentoses [70].



Figure 11. Xylose conversion and FUR yield from birch hydrolysate as a function of time at 190 °C under microwave irradiation. Biphasic reaction system: Aqueous phase = hydrolysate liquor after filtration (1.5 ml), organic phase: CPME (1.5 ml). The lines are to guide the eye.

Conclusion

In a two-phase system with three different water-immiscible organic solvents, the dehydration reaction of xylose and the resulting furfural yields were investigated under well-controlled conditions.

The optimum aqueous-to-organic phase ratio for all three tested organic solvents was 1:1 to extract FUR in the dehydration of xylose. The main product of auto-catalyzed and solid acid-catalyzed xylose dehydration was FUR, whose maximum mole fraction yield at 190

°C in 180 min was 78% in the case of CPME as an organic solvent phase. The highest selectivity to FUR, namely 93%, was achieved in 90 min at 170 °C when CPME was added.

In the case of birch hydrolysate as pentose source, a maximum FUR yield of 68% (and a xylose conversion of 96%) after 90 min autocatalyzed reaction at 190 °C was achieved under the optimized conditions of a two-phase dehydration reaction in the presence of CPME in a volume ratio of 1:1.

The results of the experiments when using isophorone as organic solvent allowed us to conclude that there are decomposition reactions between the solvent and FUR above 110 °C, which may or may not be linked to an increase on water solubility at elevated temperatures. Therefore, even though isophorone shows a higher partition coefficient in the biphasic system, it should be employed at temperatures below the conditions stated in the present study.

Studies on the in-situ extraction of FUR involving with solvents that are not miscible with water show a high selectivity to FUR and thus increase its yield. This offers an interesting approach for a greener process and the avoidance of salt addition.

Acknowledgements

This research has been done in collaboration with Stora Enso and funded through Erasmus Mundus Joint Doctoral Programme SELECT+, the support of which is gratefully acknowledged. The authors are also grateful for the support of the staff at the Department of Bioproducts and Biosystems at Aalto University especially to Heidi Meriö-Talvio and Mika Sipponen. JL is a Serra Húnter Fellow and is grateful to ICREA Academia program.

Reference List

[1] L. Filiciotto, A.M. Balu, J.C. Van der Waal, R. Luque, Catalytic insights into the production of biomass-derived side products methyl levulinate, furfural and humins, Catalysis Today. 302 (2018) 2-15.

[2] A. Griebl, T. Lange, H. Weber, W. Milacher, H. Sixta, Xylo-Oligosaccharide (XOS) Formation through Hydrothermolysis of Xylan Derived from Viscose Process, Macromol. Symp. 232 (2006) 107-120.

[3] L. Yang, J. Su, S. Carl, J.G. Lynam, X. Yang, H. Lin, Catalytic conversion of hemicellulosic biomass to lactic acid in pH neutral aqueous phase media, Applied Catalysis B: Environmental. 162 (2015) 149-157.

[4] T. Werpy, G. Petersen, Top Value Added Chemicals from Biomass: Volume I --Results of Screening for Potential Candidates from Sugars and Synthesis Gas; Sponsor Org.: US Department of Energy (US), (2004).

[5] S. Peleteiro, S. Rivas, J.L. Alonso, V. Santos, J.C. Parajó, Furfural production using ionic liquids: A review, Bioresource Technology. 202 (2016) 181-191.

[6] R.F. Perez, S.J. Canhaci, L.E.P. Borges, M.A. Fraga, One-step conversion of xylose to furfuryl alcohol on sulfated zirconia-supported Pt catalyst—Balance between acid and metal sites, Catalysis Today. 289 (2017) 273-279.

[7] X. Chen, L. Zhang, B. Zhang, X. Guo, X. Mu, Highly selective hydrogenation of furfural to furfuryl alcohol over Pt nanoparticles supported on g-C3N4 nanosheets catalysts in water, Scientific Reports. 6 (2016) 28558.

[8] K.J. Zeitsch, 14. Applications of furfural, in: K.J. Zeitsch (Ed.), The Chemistry and Technology of Furfural and its Many by-Products, Elsevier B.V., 2000, pp. 98-103.

[9] R. Mariscal, P. Maireles-Torres, M. Ojeda, I. Sadaba, M. Lopez Granados, Furfural: a renewable and versatile platform molecule for the synthesis of chemicals and fuels, Energy Environ. Sci. 9 (2016) 1144-1189.

[10] B. Kamm, P.R. Gruber, M. Kamm, Biorefineries - Industrial Processes and Products: Status Quo and Future Directions, Wiley-VCH, 2010.

[11] S.B. Kim, S.J. You, Y.T. Kim, S. Lee, H. Lee, K. Park, E.D. Park, Dehydration of Dxylose into furfural over H-zeolites, Korean Journal of Chemical Engineering. 28 (2011) 710-716.

[12] F. Xue, C. Miao, Y. Yue, W. Hua, Z. Gao, Direct conversion of bio-ethanol to propylene in high yield over the composite of In2O3 and zeolite beta, Green Chem. 19 (2017) 5582-5590.

[13] S.M. Bruce, Z. Zong, A. Chatzidimitriou, L.E. Avci, J.Q. Bond, M.A. Carreon, S.G. Wettstein, Small pore zeolite catalysts for furfural synthesis from xylose and switchgrass in a γ -valerolactone/water solvent, Journal of Molecular Catalysis A: Chemical. 422 (2016) 18-22.

[14] T. Ennaert, J. Van Aelst, J. Dijkmans, R. De Clercq, W. Schutyser, M. Dusselier, D. Verboekend, B.F. Sels, Potential and challenges of zeolite chemistry in the catalytic conversion of biomass, Chem. Soc. Rev. 45 (2016) 584-611.

[15] L.J. Konwar, P. Mäki-Arvela, E. Salminen, N. Kumar, A.J. Thakur, J. Mikkola, D. Deka, Towards carbon efficient biorefining: Multifunctional mesoporous solid acids obtained from biodiesel production wastes for biomass conversion, Applied Catalysis B: Environmental. 176–177 (2015) 20-35.

[16] P.S. Metkar, E.J. Till, D.R. Corbin, C.J. Pereira, K.W. Hutchenson, S.K. Sengupta, Reactive distillation process for the production of furfural using solid acid catalysts, Green Chem. 17 (2015) 1453-1466.

[17] M. Paniagua, S. Saravanamurugan, M. Melian-Rodriguez, J.A. Melero, A. Riisager, Xylose Isomerization with Zeolites in a Two-Step Alcohol–Water Process, ChemSusChem. 8 (2015) 1088-1094.

[18] J. Lessard, J. Morin, J. Wehrung, D. Magnin, E. Chornet, High Yield Conversion of Residual Pentoses into Furfural via Zeolite Catalysis and Catalytic Hydrogenation of Furfural to 2-Methylfuran, Topics in Catalysis. 53 (2010) 1231-1234.

[19] L.R. Ferreira, S. Lima, P. Neves, M.M. Antunes, S.M. Rocha, M. Pillinger, I. Portugal, A.A. Valente, Aqueous phase reactions of pentoses in the presence of nanocrystalline zeolite beta: Identification of by-products and kinetic modelling, Chem. Eng. J. 215–216 (2013) 772-783.

[20] S. Lima, M.M. Antunes, A. Fernandes, M. Pillinger, M.F. Ribeiro, A.A. Valente, Catalytic cyclodehydration of xylose to furfural in the presence of zeolite H-Beta and a micro/mesoporous Beta/TUD-1 composite material, Applied Catalysis A: General. 388 (2010) 141-148.

[21] B. Garg, T. Bisht, Y. Ling, Graphene-Based Nanomaterials as Heterogeneous Acid Catalysts: A Comprehensive Perspective, Molecules. 19 (2014).

[22] E. Lam, J.H. Chong, E. Majid, Y. Liu, S. Hrapovic, A.C.W. Leung, J.H.T. Luong, Carbocatalytic dehydration of xylose to furfural in water, Carbon. 50 (2012) 1033-1043.

[23] S. Suganuma, K. Nakajima, M. Kitano, H. Kato, A. Tamura, H. Kondo, S. Yanagawa, S. Hayashi, M. Hara, SO3H-bearing mesoporous carbon with highly selective catalysis, Microporous and Mesoporous Materials. 143 (2011) 443-450.

[24] E. Lam, E. Majid, A.C.W. Leung, J.H. Chong, K.A. Mahmoud, J.H.T. Luong, Synthesis of Furfural from Xylose by Heterogeneous and Reusable Nafion Catalysts, ChemSusChem. 4 (2011) 535-541.

[25] A.S. Dias, S. Lima, M. Pillinger, A.A. Valente, Modified versions of sulfated zirconia as catalysts for the conversion of xylose to furfural, Catalysis Letters. 114 (2007) 151-160.

[26] S.J. You, Y.T. Kim, E.D. Park, Liquid-phase dehydration of d-xylose over silicaalumina catalysts with different alumina contents, Reaction Kinetics, Mechanisms and Catalysis. 111 (2014) 521-534.

[27] E. Sairanen, K. Vilonen, R. Karinen, J. Lehtonen, Functionalized Activated Carbon Catalysts in Xylose Dehydration, Topics in Catalysis. 56 (2013) 512-521.

[28] V.K. Ahluwalia, M. Kidwai, Basic Principles of Green Chemistry, in: V.K. Ahluwalia, M. Kidwai (Eds.), New Trends in Green Chemistry, Springer Netherlands, Dordrecht, 2004, pp. 5-14.

[29] I. van Zandvoort, Y. Wang, C.B. Rasrendra, E.R.H. van Eck, P.C.A. Bruijnincx, H.J. Heeres, B.M. Weckhuysen, Formation, Molecular Structure, and Morphology of Humins in Biomass Conversion: Influence of Feedstock and Processing Conditions, ChemSusChem. 6 (2013) 1745-1758.

[30] H. Rasmussen, H.R. Sørensen, A.S. Meyer, Formation of degradation compounds from lignocellulosic biomass in the biorefinery: sugar reaction mechanisms, Carbohydr. Res. 385 (2014) 45-57.

[31] C. Sener, A.H. Motagamwala, D.M. Alonso, J.A. Dumesic, Enhanced furfural yields from xylose dehydration in the γ -valerolactone/water solvent system at elevated temperatures, ChemSusChem. 11 (2018) 2321.

[32] M.A. Mellmer, C. Sener, J.M.R. Gallo, J.S. Luterbacher, D.M. Alonso, J.A. Dumesic, Solvent Effects in Acid-Catalyzed Biomass Conversion Reactions, Angewandte Chemie International Edition. 53 (2014) 11872-11875.

[33] G. Gómez Millán, Z. El Assal, K. Nieminen, S. Hellsten, J. Llorca, H. Sixta, Fast furfural formation from xylose using solid acid catalysts assisted by a microwave reactor, Fuel Process Technol. 182 (2018) 56-67.

[34] R. Weingarten, J. Cho, J. Conner Wm.Curtis, G.W. Huber, Kinetics of furfural production by dehydration of xylose in a biphasic reactor with microwave heating, Green Chem. 12 (2010) 1423-1429.

[35] F. Trimble, A.P. Dunlop, Recovery of Furfural from Aqueous Solutions, Ind. Eng. Chem. Anal. Ed. 12 (1940) 721-722.

[36] E.I. Gürbüz, S.G. Wettstein, J.A. Dumesic, Conversion of Hemicellulose to Furfural and Levulinic Acid using Biphasic Reactors with Alkylphenol Solvents, ChemSusChem. 5 (2012) 383-387.

[37] J. Zhang, J. Zhuang, L. Lin, S. Liu, Z. Zhang, Conversion of D-xylose into furfural with mesoporous molecular sieve MCM-41 as catalyst and butanol as the extraction phase, Biomass and Bioenergy. 39 (2012) 73-77.

[38] P.L. Dhepe, R. Sahu, A solid-acid-based process for the conversion of hemicellulose, Green Chem. 12 (2010) 2153-2156.

[39] A. Mittal, S.K. Black, T.B. Vinzant, M. O'Brien, M.P. Tucker, D.K. Johnson, Production of Furfural from Process-relevant Biomass-derived Pentoses in a Biphasic Reaction System, ACS Sustainable Chem. Eng. (2017).

[40] A.S. Dias, S. Lima, M. Pillinger, A.A. Valente, Acidic cesium salts of 12tungstophosphoric acid as catalysts for the dehydration of xylose into furfural, Carbohydrate Research. 341 (2006) 2946-2953.

[41] X. Guo, F. Guo, Y. Li, Z. Zheng, Z. Xing, Z. Zhu, T. Liu, X. Zhang, Y. Jin, Dehydration of D-xylose into furfural over bimetallic salts of heteropolyacid in DMSO/H2O mixture, Applied Catalysis A: General. 558 (2018) 18-25.

[42] H. Li, A. Deng, J. Ren, C. Liu, W. Wang, F. Peng, R. Sun, A modified biphasic system for the dehydration of d-xylose into furfural using SO42–/TiO2-ZrO2/La3+ as a solid catalyst, Catalysis Today. 234 (2014) 251-256.

[43] D.M. Argyle, H.C. Bartholomew, Heterogeneous Catalyst Deactivation and Regeneration: A Review, Catalysts. 5 (2015).

[44] J.E. Romo, N.V. Bollar, C.J. Zimmermann, S.G. Wettstein, Conversion of Sugars and Biomass to Furans Using Heterogeneous Catalysts in Biphasic Solvent Systems, ChemCatChem. 10 (2018) 4805-4816.

[45] K. Watanabe, The Toxicological Assessment of Cyclopentyl Methyl Ether (CPME) as a Green Solvent, Molecules. 18 (2013).

[46] S. Tenne, J. Kinzel, M. Arlt, F. Sibilla, M. Bocola, U. Schwaneberg, 2-Methyltetrahydrofuran and cyclopentylmethylether: Two green solvents for efficient purification of membrane proteins like FhuA, Journal of Chromatography B. 937 (2013) 13-17.

[47] M.J. Campos Molina, R. Mariscal, M. Ojeda, M. López Granados, Cyclopentyl methyl ether: A green co-solvent for the selective dehydration of lignocellulosic pentoses to furfural, Bioresour. Technol. 126 (2012) 321-327.

[48] S. Tenne, U. Schwaneberg, First Insights on Organic Cosolvent Effects on FhuA Wildtype and FhuA Δ 1-159, Int J Mol Sci. 13 (2012).

[49] O. Ershova, J. Pokki, A. Zaitseva, V. Alopaeus, H. Sixta, Vapor pressure, vaporliquid equilibria, liquid-liquid equilibria and excess enthalpy of the system consisting of isophorone, furfural, acetic acid and water, Chemical Engineering Science. 176 (2018) 19-34.

[50] M. Männistö, J. Pokki, V. Alopaeus, Quaternary and ternary LLE measurements for solvent (2-methyltetrahydrofuran and cyclopentyl methyl ether) + furfural + acetic acid + water between 298 and 343 K, The Journal of Chemical Thermodynamics. 119 (2018) 61-75.

[51] V. Pace, W. Holzer, P. Hoyos, M.J. Hernáiz, A.R. Alcántara, 2-Methyltetrahydrofuran, in: P.L. Fuchs (Ed.), Encyclopedia of Reagents for Organic Synthesis, John Wiley & Sons, Ltd, 2001, pp. 1-6.

[52] K. Lamminpää, J. Ahola, J. Tanskanen, Kinetics of Xylose Dehydration into Furfural in Formic Acid, Ind Eng Chem Res. 51 (2012) 6297-6303.

[53] K. Dussan, B. Girisuta, M. Lopes, J.J. Leahy, M.H.B. Hayes, Effects of Soluble Lignin on the Formic Acid-Catalyzed Formation of Furfural: A Case Study for the Upgrading of Hemicellulose, ChemSusChem. 9 (2016) 492-504.

[54] A. Sluiter, B. Hames, R. Ruiz, C. Scarlata, J. Sluiter, D. Templeton, Determination of Sugars, Byproducts, and Degradation Products in Liquid Fraction Process Samples, Technical Report NREL/TP-510-42623. (2008).

[55] S. Givry, C. Bliard, F. Duchiron, Selective ketopentose analysis in concentrate carbohydrate syrups by HPLC, Carbohydr. Res. 342 (2007) 859-864.

[56] C. Pirola, I. Rossetti, V. Ragaini, Are conversion, selectivity and yield terms unambiguously defined in chemical and chemical engineering technology? La Chimica & L'Industria. 2 (2013) 136-145.

[57] M. Männistö, J. Pokki, L. Fournis, V. Alopaeus, Ternary and binary LLE measurements for solvent (2-methyltetrahydrofuran and cyclopentyl methyl ether)+furfural+water between 298 and 343K, The Journal of Chemical Thermodynamics. 110 (2017) 127-136.

[58] S.L. Guenic, F. Delbecq, C. Ceballos, C. Len, Microwave-assisted dehydration of D-xylose into furfural by diluted inexpensive inorganic salts solution in a biphasic system, Journal of Molecular Catalysis A: Chemical. 410 (2015) 1-7.

[59] B. Danon, W. Hongsiri, L. van der Aa, W. de Jong, Kinetic study on homogeneously catalyzed xylose dehydration to furfural in the presence of arabinose and glucose, Biomass Bioenergy. 66 (2014) 364-370.

[60] O. Ershova, J. Kanervo, S. Hellsten, H. Sixta, The role of xylulose as an intermediate in xylose conversion to furfural: insights via experiments and kinetic modelling, RSC Adv. 5 (2015) 66727-66737.

[61] S. Le Guenic, D. Gergela, C. Ceballos, F. Delbecq, C. Len, Furfural Production from d-Xylose and Xylan by Using Stable Nafion NR50 and NaCl in a Microwave-Assisted Biphasic Reaction, Molecules. 21 (2016).

[62] G. Marcotullio, W. de Jong, M.A. Tavares Cardoso, A.H.M. Verkooijen, Bioenergy II: Furfural Destruction Kinetics during Sulphuric Acid-Catalyzed Production from Biomass, International Journal of Chemical Reactor Engineering. 7(1):A67 (2009).

[63] B. Danon, L. van der Aa, W. de Jong, Furfural degradation in a dilute acidic and saline solution in the presence of glucose, Carbohydrate Research. 375 (2013) 145-152.

[64] K. Lamminpää, J. Ahola, J. Tanskanen, Kinetics of furfural destruction in a formic acid medium, RSC Adv. 4 (2014) 60243-60248.

[65] S. Thiyagarajan, H.C. Genuino, M. Sliwa, van der Waal, Jan C., E. de Jong, J. van Haveren, B.M. Weckhuysen, P.C.A. Bruijnincx, D.S. van Es, Substituted Phthalic Anhydrides from Biobased Furanics: A New Approach to Renewable Aromatics, ChemSusChem. 8 (2015) 3052-3056.

[66] T. Shanmugam, H.C. Genuino, J.C. van der Waal, E. de Jong, B.M. Weckhuysen, J. van Haveren, P.C. Bruijnincx, D.S. van Es, A Facile Solid-Phase Route to Renewable Aromatic Chemicals from Biobased Furanics, Angew. Chem. Int. Ed. 55 (2016) 1368-1371.

[67] H.C. Genuino, T. Shanmugam, J.C. van der Waal, E. deJong, J. van Haveren, D.S. van Es, B.M. Weckhuysen, P.C. Bruijnincx, Selectivity Control in the Tandem Aromatization of Bio-Based Furanics Catalyzed by Solid Acids and Palladium, ChemSusChem. 10 (2017) 277-286.

[68] A.W.T. King, V. Mäkelä, S.A. Kedzior, T. Laaksonen, G.J. Partl, S. Heikkinen, H. Koskela, H.A. Heikkinen, A.J. Holding, E.D. Cranston, I. Kilpeläinen, Liquid-State NMR Analysis of Nanocelluloses, Biomacromolecules. (2018).

[69] D.C. Rideout, R. Breslow, Hydrophobic Acceleration of Diels-Alder Reactions, J. Am. Chem. Soc. 102 (1980) 7817-7818.

[70] O. Ershova, K. Nieminen, H. Sixta, The Role of Various Chlorides on Xylose Conversion to Furfural: Experiments and Kinetic Modeling, ChemCatChem. 9 (2017) 3031-3040.