



This is an electronic reprint of the original article. This reprint may differ from the original in pagination and typographic detail.

Tran, Minh-Quang; Elsisi, Mahmoud; Mahmoud, Karar; Liu, Meng-Kun; Lehtonen, Matti; Darwish, Mohamed M. F.

Experimental Setup for Online Fault Diagnosis of Induction Machines via Promising IoT and Machine Learning: Towards Industry 4.0 Empowerment

Published in: **IEEE** Access

DOI: 10.1109/ACCESS.2021.3105297

Published: 01/08/2021

Document Version Publisher's PDF, also known as Version of record

Published under the following license: CC BY

Please cite the original version: Tran, M.-Q., Elsisi, M., Mahmoud, K., Liu, M.-K., Lehtonen, M., & Darwish, M. M. F. (2021). Experimental Setup for Online Fault Diagnosis of Induction Machines via Promising IoT and Machine Learning: Towards Industry 4.0 Empowerment. *IEEE Access*, *9*, 115429-115441. Article 9514571. https://doi.org/10.1109/ACCESS.2021.3105297

This material is protected by copyright and other intellectual property rights, and duplication or sale of all or part of any of the repository collections is not permitted, except that material may be duplicated by you for your research use or educational purposes in electronic or print form. You must obtain permission for any other use. Electronic or print copies may not be offered, whether for sale or otherwise to anyone who is not an authorised user.



Received June 1, 2021, accepted August 12, 2021, date of publication August 16, 2021, date of current version August 25, 2021. Digital Object Identifier 10.1109/ACCESS.2021.3105297

# **Experimental Setup for Online Fault Diagnosis of Induction Machines via Promising IoT and Machine Learning: Towards Industry 4.0 Empowerment**

MINH-QUANG TRAN<sup>®1, 2</sup>, MAHMOUD ELSISI<sup>®1, 3</sup>, KARAR MAHMOUD<sup>®4, 5</sup>, MENG-KUN LIU<sup>®1,6</sup>, MATTI LEHTONEN<sup>®4</sup>, AND MOHAMED M. F. DARWISH<sup>®3,4</sup>

<sup>1</sup>Industry 4.0 Implementation Center, Center for Cyber-Physical System Innovation, National Taiwan University of Science and Technology,

Taipei City 10607, Taiwan

<sup>2</sup>Department of Mechanical Engineering, Thai Nguyen University of Technology, Thái Nguyên 250000, Vietnam

<sup>3</sup>Department of Electrical Engineering, Faculty of Engineering at Shoubra, Benha University, Cairo 11629, Egypt

<sup>4</sup>Department of Electrical Engineering and Automation, School of Electrical Engineering, Aalto University, 02150 Espoo, Finland

<sup>5</sup>Department of Electrical Engineering, Faculty of Engineering, Aswan University, Aswan 81542, Egypt

<sup>6</sup>Department of Mechanical Engineering, National Taiwan University of Science and Technology, Taipei City 10607, Taiwan

Corresponding authors: Karar Mahmoud (karar.mostafa@aalto.fi) and Mohamed M. F. Darwish (mohamed.m.darwish@aalto.fi; hamed.darwish@feng.bu.edu.eg)

This work was supported in part by the Department of Electrical Engineering and Automation, Aalto University, Espoo, Finland, and in part by the Center for Cyber-physical System Innovation from the Featured Areas Research Center Program in the Agenda of the Higher Education Sprout Project, Taiwan.

**ABSTRACT** In recent years, the internet of things (IoT) represents the main core of Industry 4.0 for cyber-physic systems (CPS) in order to improve the industrial environment. Accordingly, the application of IoT and CPS has been expanded in applied electrical systems and machines. However, cybersecurity represents the main challenge of the implementation of IoT against cyber-attacks. In this regard, this paper proposes a new IoT architecture based on utilizing machine learning techniques to suppress cyber-attacks for providing reliable and secure online monitoring for the induction motor status. In particular, advanced machine learning techniques are utilized here to detect cyber-attacks and motor status with high accuracy. The proposed infrastructure validates the motor status via communication channels and the internet connection with economical cost and less effort on connecting various networks. For this purpose, the CONTACT Element platform for IoT is adopted to visualize the processed data based on machine learning techniques through a graphical dashboard. Once the cyber-attacks signal has been detected, the proposed IoT platform based on machine learning will be visualized automatically as fake data on the dashboard of the IoT platform. Different experimental scenarios with data acquisition are carried out to emphasize the performance of the suggested IoT topology. The results confirm that the proposed IoT architecture based on the machine learning technique can effectively visualize all faults of the motor status as well as the cyber-attacks on the networks. Moreover, all faults of the motor status and the fake data, due to the cyber-attacks, are successfully recognized and visualized on the dashboard of the proposed IoT platform with high accuracy and more clarified visualization, thereby contributing to enhancing the decision-making about the motor status. Furthermore, the introduced IoT architecture with Random Forest algorithm provides an effective detection for the faults on motor due to the vibration under industrial conditions with excellent accuracy of 99.03% that is significantly greater than the other machine learning algorithms. Besides, the proposed IoT has low latency to recognize the motor faults and cyber-attacks to present them in the main dashboard of the IoT platform.

**INDEX TERMS** Fault diagnosis, induction motor, machine learning, Internet of Things, industry 4.0.

#### I. INTRODUCTION

The associate editor coordinating the review of this manuscript and approving it for publication was Razi Iqbal<sup>(D)</sup>.

Worldwide, since the industrial revolution, rotary equipment has been widely used in many areas. Among them, induction

motors play an essential role in the industry due to their low cost, easy maintenance, and unrestricted working environment [1]. However, if the production line is unpredictably shut down because of sudden failures of motors, it causes heavy damage over time. Therefore, fault detection and diagnosis for induction motors become much more important. The motor failures would generate heat and vibration and increase energy consumption [2]. As a result, the motor life would be reduced. There are many kinds of motor failures which are categorized into two major types of faults including electrical faults and mechanical faults. Mechanical faults include bearing faults, misalignment faults, and air-gap eccentricity faults. While electrical faults are related to faults like stator short-circuits, broken bar faults, and end ring faults [3], [4]. Bearings are among the most important components in induction machines. Their load capability, running accuracy, noise levels, frictional heat, and useful life will directly affect the induction machines [5]. It is about 40% - 90% of all motor failures that come from bearing faults depending on the size of the motors [6]. Therefore, the early detection and diagnosis of bearing faults could prevent sudden failure. This research subject still attracts great attention from the research community.

The diagnosis method can be divided into vibration and current analysis. The approach based on the motor current signature analysis (MCSA) is considered because of its lowcost, non-intrusive, and fast installation [7], [8]. However, the current signal diagnosis is difficult to detect abnormalities in the early stage of motor failures, this approach is still an immature technology compared to the vibration signal diagnosis [9]. According to the specification of ISO-10816 [10], it proposed a method for evaluating the statuses of the motor based on the measured vibration signal. A threshold for vibration damage has been proposed for motor condition monitoring. The method based on the curve component analysis was proposed to analyze vibration characteristics and to establish nonlinear data for the training dataset [11]. The individual frequency bands for envelope spectrum analysis can be extracted by filtering the vibration signal with the appropriate bandwidth. Then, the characteristic frequencies of the vibration signals can be observed in the initial stage of the bearing fault [12]. Statistical calculations were used to calculate the measured vibration energy. The influence of bearing speed on statistical indicators has been introduced, it showed that the kurtosis and skewness factors can be effective parameters for bearing defect identification [13].

Signal analysis approaches have been widely used to study motor signal vibration for bearing fault diagnosis. An improved fast Fourier transform for vibration signal analysis was introduced for both simulation and practical applications [14]. Several time-frequency analysis approaches were utilized for fault diagnoses such as the short-time Fourier Transform (STFT), Wavelet Transform (WT), and the Hilbert-Huang Transform (HHT). The WT could provide a good resolution for both time and frequency domain that overcome the limitation of the STFT, thus the method is widely used for fault diagnosis [15], [16]. In addition to Fourier transform and WT, the HHT is also an effective approach for motor vibration signal analysis, it can detect malfunctioning by revealing the instantaneous amplitude and nonlinear and nonstationary characteristics in the frequency content [17]. Furthermore, the vibration signal contaminated by signal noise could be filtered by using the wavelet packet decomposition (WPD), the energy of the WPD coefficients could be utilized to detect the rolling bearing failures effectively [18]. The WPD and statistical methods were developed to successfully extract the significant features of bearing faults using time-frequency analysis [19].

Recently, fault diagnosis and detection based on artificial machine learning techniques have been performed effectively [20]. These methods usually involve intelligent signal analysis and it requires data collection to do signal processing and feature extraction. Various classifiers including artificial neural networks, k-nearest neighbors (kNN), and support vector machines (SVM) have been applied to fuse the vibration and current signal for multi-faults classification of induction motor [9]. Yang et al. [21] proposed a method based on a random forest (RF) algorithm that can achieve satisfactory accuracy for machine fault diagnosis with fast execution speed. The performance of the proposed method is much better compared to the other classifiers such as kNN, SVM, and decision tree. The machine learning ensemble classifier including RF and extreme gradient boosting (XGBoost) could be a promising model in terms of accuracy for bearing fault diagnosis [22], [23]. However, it is still difficult to determine features that are the most sensitive to the fault of the induction machine, because the performance of machine learning techniques is reflected by choosing suitable fault features. Deep learning can extract and learn the representative patterns of the signals effectively compared to conventional feature extraction and selection methods. For example, the convolutional neural network method shows excellent performance for pattern recognition that was also applied for fault diagnosis [24], [25]. Janssens *et al.* developed an architecture of the CNN model for detecting rotary machinery faults with vibration spectrum features [26]. However, the computational time is one of the most challenging to apply deep learning for online condition monitoring. Thus, an appropriate machine learning approach still needs to investigate to enhance the performance of the model with high accuracy and short computational time. The authors of [27] have investigated the cloud-based malware detection game, where mobile devices divest their application traces to security servers through base stations or access points.

Nowadays, the development of Industry 4.0 and the rise of the Internet of things (IoT) have become a solution for advanced predictive maintenance applications, in which the status of the motor is constantly monitored and recorded [28]. The concept of industrial IoT has been considered in many industrial fields and is expected to drive industry growth. The industrial IoT concept involves smart machines that are



FIGURE 1. Industrial IoT architecture for condition monitoring of induction motors.

equipped with different sensors, connectivity, data management, and application layer as shown in Fig. 1 [29]. The sensor data analytics and management of big data are both challenging tasks of IoT, particularly for online condition monitoring of the IoT system [30]. IoT system allows the user able to monitor the machine status in real-time and it can give quick feedback with proper adjustments [31]. Thus, it can help to accelerate the operation of the factories that involve diverse electrical machines, mostly induction motors.

As aforementioned in the literature, effective monitoring bearing faults are considered the main challenges of the rotary equipment to enhance the efficiency of the operation and lifetime of the induction machines. This study was inspired by the development of IoT and machine learning approaches that towards intelligence industrial machine. To the best of the authors' knowledge, this is the first study to experimentally apply IoT and CPS concepts to effectively diagnose induction motor faults with data acquisition. Specifically, an intelligence IoT platform integrating an improved machine learning algorithm is developed to detect the bearing fault of the induction motor. Besides, the powerful learning ability of the machine learning model enables the proposed system to detect fake data considered as cyber-attack accurately.

The contributions of this paper are summarized in the following points,

- Developing a cheap and easy implementation IoT architecture with machine learning techniques for motor faults detection instead of the traditional fault's detection schemes for induction machines.
- The introduced IoT architecture with machine learning algorithms can also detect the cyber-attack and present it as fake data in the main dashboard of the IoT platform to provide secure online monitoring.
- The proposed infrastructure can detect the normal, inner bearing defect, outer bearing defect in order to maintain a healthy state and increase the lifetime of the induction machines.

- The proposed IoT has low latency to recognize the motor faults and cyber-attacks to present them in the main dashboard of the IoT platform.
- The experimental results indicate the superiority of the proposed IoT system integrating machine learning for condition monitoring of the induction machines.

The remainder of the paper is organized as follows. The proposed industrial IoT architecture and machine learning algorithms are described in Sections II and III. Simulation results are presented in Section IV. The conclusions drawn from the result section are summarized in Section V.

# **II. PROPOSED INDUSTRIAL IOT ARCHITECTURE**

#### A. ARCHITECTURE OVERVIEW

The extension of the IoT in industrial applications is namely industrial internet of things (IIoT) which refers to the communication of machine-to-machine (M2M), data analysis, and machine learning. Recently, Industrial IoT has been considered in many applications towards smart factories to get high performance, more efficiency, and reliability in their operations [32]. An architecture of IIoT for condition monitoring of induction motors is proposed in Fig. 2. The induction machines are equipped with sensors to continuously collect the data. Then, the sensor data is transmitted on the cloud layer through the connectivity layer with the IoT gateway. To manage the sensor data, the software part is required, then the large volumes of sensor data can be stored and analyzed in real-time. Finally, the decision-making is carried out before any necessary actions feedback to the machine. Cloud computing to process the data can be accelerated by artificial intelligence and machine learning that allow to improve the performance and reduce the computational time of the system. In the application layer, a user interface is designed to visualize data analytics and remote data monitoring in realtime. In this paper, the CONTACT Elements for IoT using the standard MQTT protocol is proposed to visualize such information through a graphical dashboard [33]. The proposed



FIGURE 2. Proposed IoT architecture for online monitoring of the induction motor.

IIoT is integrated with a machine learning approach for condition monitoring of induction motor. Furthermore, the fake data due to the cyber-attack is usually the main challenge against the visualization of the real data. The cyber-attack needs to be detected in order to provide the user with real data that allows reliable decision-making and keeps the operation of the motor in a healthy condition.

#### **B. EXPERIMENTAL SETUP AND DATA ACQUISITION**

In this section, the experimental setup and data acquisition for the induction motor is presented. Figure 3 shows the motordriven rotary system that includes a TECO AEHF 3-phase induction, a TECO A510 series variable frequency drive, and a Chain Tail ZKB010AA magnetic particle brake. The Torque values applied on the motor were controlled using a torque meter with the type of Lorenz Dr-2477-P. The vibration signal was measured by the Wilcoxon 786A accelerometers with a sampling rate of 25,600 samples/sec. Several bearing conditions including healthy condition, outer ring fault, and inner ring fault were conducted in the experiment. Additionally, fake data is also considered in this study as a cyberattack. Figure 4 describes the outer ring and inner ring defects with 0.2 mm depth and 0.2 mm width were created by making a groove in each ring using wire electrical discharge machining.

A series of six-type experiment was conducted with three different bearing conditions, in which two different rotational speed, three electricity modes, and three resistance conditions were applied to the induction motor operations. The details of each condition are listed in Table 1. A LabVIEW program was developed to capture the vibration signals under different bearing conditions including normal condition, inner ring

IADLE 1. Parameters of the experimental set	TABLE	1.	Parameters	of the	experimental	setup
---	-------	----	------------	--------	--------------	-------

Experiment design	Rotation speed (rpm)	Eccentricity mode	Resistance (N-m)	Failure condition
1	1350	Parallel	3.0	Normal
2	1350	Angle	0.3	Inner ring fault
3	1350	Normal	1.5	Outer ring fault
4	1800	Angle	1.5	Normal
5	1800	Normal	3.0	Inner ring fault
6	1800	Parallel	0.3	Outer ring fault

fault, and outer ring fault. The vibration signal was measured once the motor speed reached a steady state. Each bearing condition was recorded for a span of 20 s and it was repeated three times for each experiment condition.

The characteristic frequencies of the bearing faults can be described by Eqs. (1) and (2).

$$f_{ORF} = \frac{N_B}{2} f_R \left( 1 - \frac{D_B \cos(\theta)}{D_P} \right) \tag{1}$$

$$f_{IRF} = \frac{N_B}{2} f_R \left( 1 + \frac{D_B \cos(\theta)}{D_P} \right) \tag{2}$$

where  $f_{ORF}$  and  $f_{ORF}$  are the characteristic frequencies of the outer bearing fault and inner bearing fault.  $N_B$  is the number



FIGURE 3. Experimental motor-driven rotary system setup.



FIGURE 4. Motor defects; (a) Outer ring defect, and (b) Inner ring defect.

of balls,  $D_P$  is the pitch diameter,  $D_B$  is the ball diameter,  $\theta$  is the contact angle, and  $f_R$  is the rotation speed. The 6204-T1 bearing was used in this experiment, the parameters and dimensions of the roller bearing are described in [19]. The vibration signal of each experiment was collected and labeled for each bearing condition. The time-domain spectrum of measured vibration signals under different bearing conditions is presented in Fig. 5. It shows that when the bearing failures occur, the vibration amplitudes are significantly increased in the time response compared to the response of healthy bearing. Moreover, different periods of shockwave are also observed in the cases of the inner ring and outer ring defects owing to the collision of the balls and the defect on the rings, as shown in Figs. 5 (b) and (c).

## **III. MACHINE LEARNING ALGORITHMS**

Recently, machine learning approaches have been applied to different engineering applications [34]–[37], which in turn have been widely used for bearing diagnosis of induction machines. These methods can reduce the memory computation while remaining high classification accuracy. It shows advantages comparing to linear models [38]–[41]. There are several different machine learning algorithms for classification problems. In this study, three effective ensemble methods machine learning techniques including



FIGURE 5. Measurement of vibration signal under different conditions (a) healthy bearing, (b) inner ring fault, and (c) outer ring fault.

decision tree (DT), random forest (RF), and extreme gradient boosting (XGBoost) algorithms are used to distinguish different bearing conditions. Those algorithms can perform very well on the respective data, particularly on the time series. They have shown effectiveness in terms of high accuracy at fast speed. Moreover, three approaches can reduce overfitting issues that make them more suitable when applying for fault detection problems compared to other machine learning algorithms such as the SVM algorithm [42].

#### A. DECISION TREE

The DT method is one of the supervised learning algorithms, in which a training model is created to estimate the target from unseen samples by learning simple decision rules [43], [44]. The DT algorithm has a fast training process with low memory requirements. In the training process, to estimate the class of the given dataset, first, the values of the root attribute are compared to the real dataset attribute. The algorithm continues to compare the attribute value with the other sub-nodes in the next node and moves further. Finally, the process reaches the leaf node of the tree. Figure 6 presents the structure of the decision tree algorithm.





FIGURE 6. Structure of decision tree.

Suppose the training set is S and the attribute of target possesses n different values, the entropy of the training set S is described in Eq. (3).

$$Entropy(S) = \sum_{i=1}^{n} p_i log_2^{p_i},$$
(3)

where  $p_i$  represents the proportion of the  $i^{th}$  attribute value.

The information gain of an attribute that describes the decrease of expected entropy is defined in Eq. (4).

Gain (S, V) = Entropy (S) - 
$$\sum_{a \in A(V)} \frac{|S_a|}{|S|} Entropy(S_a),$$
(4)

where A(V) shows the range of the attribute A and  $S_a$  describes the sample set, in which the attribute V has the value of a.

In this work, a time series data set is used as an attribute or feature vector, which represents the vibration data points of a period of time. The proposed decision tree model uses the information gain, as shown in Eq. (4) to define an attribute from the attribute vector that gives maximum information about a bearing condition. The attribute with the largest information gain is selected to be the decision attribute for the node. Therefore, the level of entropy can be decreased from the root node to the leaf node.

# **B. RANDOM FOREST**

The random forest (RF) is also known as an effective method for fault diagnosis problems. The RF is an ensemble approach that uses tree-type classifiers. This method can enhance the performance of the model by using bagging to suppress overfitting [45]. The decisions of RF are based on the total votes of component predictors from each target. Figure 7 illustrates

the structure of the random forest algorithm for ensemble decision-making.

Random forest algorithm combines many decision trees. However, an individual decision tree is now built in the forest using a random subset of attributes, and each one is trained on a random set of the training data set. Then, the prediction of the random forest model is made by average voting from every individual decision tree. Thus, the RF algorithm can reduce overfitting in decision trees. Figure 7 illustrates the structure of the random forest algorithm for ensemble decision-making. The procedure of RF starts with the selection of random samples from a training dataset of vibration signals, then the random attribute vector consists of the limited number of attributes, which is randomly generated within the subset of data to constitute the collection. The decision tree is constructed corresponding to the elements in the collection. Each decision tree has its own decision. Finally, a majority voting process is applied to determine the optimal classification result, the prediction target with the highest score is considered to be the output.

# C. EXTREME GRADIENT BOOSTING

Extreme Gradient Boosting (XGBoost) is a scalable endto-end tree boosting system introduced by Chen and Guestrin [46]. It has been widely used for fault classification problems with great performance [42], [47]. In the Gradient boosting algorithm, new models are generated to estimate the errors of previous models. Both models are combined to make the final decision, in which the stochastic gradient descent (SGD) algorithm is utilized to minimize the loss. The SGD is a very popular algorithm for optimizing an objective function using an iterative process [48]. Because the XGBoost can push the limit of computations resources for boosted tree algorithms, the number of calculations can be reduced, and the classification speed can be improved. Especially, the XGBoost classifier can suppress the overfitting problem by simplifying the objective functions. The iteration of the XGBoost algorithm starts with the first learner which is fitted to the entire data. Then, the error of the first learner will be fitted by the second learner. This process will continue the learning process and complete if a stopping condition is met. The workflow of the XGBoost classifier for motor fault diagnosis is described in Fig. 8.



FIGURE 8. Scheme of extreme gradient boosting classifier.

## **IV. RESULTS AND DISCUSSIONS**

In this study, DT, RF, and XGBoost classifiers are proposed to identify four conditions of the bearing including normal, inner bearing fault, outer bearing fault, and cyber-attack case. The measured experimental data was used to generate the dataset for training and testing processes. The sample data was generated using a window size of 2000 data points for each time series, it was labeled corresponding to each bearing condition. In this study, the experimental dataset consists of 3079 samples with multiple attributes. It includes 770 samples of normal condition, 768 samples of inner ring fault, 771 samples of outer ring fault, and 770 samples of fake data. The entire dataset is split into 70% training dataset and 30% testing dataset. Note that the dataset of 770 samples is created by a randomly distributed function within the range of the motor vibration signal to represent the fake data then it is combined with the other dataset. All data were normalized using the Min-Max Scaler, which changes all features to be between 0 and 1. Then, the data was pushed into the different training models. The training and testing models were processed using a PC computer with an Intel (R) Core<sup>TM</sup> i7-8700 @3.20 GHz central processing unit and 6G RAM.

Generally, machine learning models have two types of parameters: model parameters and hyperparameters. While the model parameters are is generated automatically by the models based on the dataset. The hyperparameters can be adjusted to setup models to improve their performance such as the learning rate parameter. Thus, the hyperparameter tuning preprocess is required to define those parameters to obtain the highest accuracy and the minimum error when constructing machine learning models. There are several optimization algorithms are used for the tuning process such as grid search and random search. The grid search is known as a great approach for hyperparameter optimization that can overcome the limitation of the manual search [49]. Therefore, the grid search algorithm is utilized to find the set of optimal hyperparameters for the RF and XGBoost models in this study. As the result of the tuning process, the hyperparameter for each model is optimized and defined. For the XGBoost model, the maximum number of iterations was optimized with "n estimators" of 400, the learning rate value is 0.1 which allows the learning speed is fast while remaining good performance of the model. The maximum depth of the tree is 4 that can control overfitting. The value of "min child weight" is 5. The learning process can be optimized using the objective function "multi: softprob". For the RF model, the maximum number of iterations was optimized with "n estimators" of 800, an entropy criterion was selected to minimize the probability of misclassification, and the number of features to consider as looking for the best split is log2. The performances of all machine learning techniques are evaluated by the following Eq. (5).

$$accuracy = \frac{TP + TN}{TP + FP + TN + FN}$$
 (5)

 $(TP = true \ positive; TN = true \ negative; FP = false \ positive; FN = false \ negative).$ 

The classification results from different proposed machine learning approaches are shown in Figs. (9-11) and summarized in Table 2. The corresponding confusion matrices of the testing dataset demonstrate that the classifiers are very successfully identifying the bearing faults and even cyber-attack presented by fake data. Moreover, Fig. 12 shows the total accuracy of each machine learning algorithm by bar chart as a clarified way for comparison. It shows that the proposed RF algorithm can provide an excellent classification accuracy of 99.03%, in which the false positive and the false negative numbers are very small. The DT approach has the worst performance with 83.33% classification accuracy. Whereas,



**FIGURE 9.** Classification result from proposed DT; (a) Confusion matrix without normalization, and (b) Confusion matrix with normalization.

Motor status Method	Normal	Outer ring faults	Inner ring faults	Attacked	Total accuracy
Decision Tree (DT)	97.59%	90.48%	96.93%	100%	83.33%
XGBoost	97.59%	90.48%	96.93%	100%	96.43%
Proposed Random Forest (RF)	99.6%	96.67%	99.56%	100%	99.03%





**FIGURE 10.** Classification result from proposed XGBoost classifier; (a) Confusion matrix without normalization, and (b) with normalization.



**FIGURE 11.** Classification result from proposed RF classifier; (a) Confusion matrix without normalization, and (b) with normalization.



FIGURE 12. The total accuracy of each machine learning algorithm.

the XGBoost algorithm can achieve higher classification accuracy, approximately 96.43%.

The receiver operating characteristic (ROC) curve and the area under the curve (AUC) are also carried to evaluate the performance of the three models, as shown in Fig. 13.

115436

The ROC curves present the performance of classification models with respect to classification thresholds, in which the true positive rate (TPR) and the false positive rate (FPR) are defined in Eq. (6). Whereas the AUC measures the area under the entire ROC curve. Therefore, the better classification model has a higher AUC, which can successfully distinguish between motor statuses at the AUC value of 1.0.

$$TPR = \frac{TP}{TP + FN}; \quad FPR = \frac{FP}{FP + FP}$$
 (6)

The ROC curves the AUC values of the DT, XGboost, and RF models for distinguishing four classes (0-normal, 1-inner ring fault, 2-outer ring fault, and 3-cyber-attack) are presented in Figs. 13 (a), (b), and (c) respectively. It confirms that the proposed RF model can successfully distinguish among the classes, in which the AUC values reach 1.0 for all classes, as shown in Fig. 13 (c). The DT model shows the worst performance, which has smallest AUC values of four classes are very small and ranging from 0.8 to 0.99, as shown in Fig. 12(a). The performance of the XGBoost model in terms of AUC is between the DT and RF approaches, as illustrated in Fig. 13 (b). In addition, micro-average and macro-average ROC are used to evaluate the imbalance of data. For macro-average, models are encouraged to focus on every class correctly. Whereas, the models are highly relying on the majority classes for micro-average. The ROC and AUC results of three models show that both macro-average and micro-average AUC values are the same in each model that indicates the balance data for four classes. It is concluded that the proposed RF approach is robust and stable for the fault classification.

After training and testing, the created model of the proposed RF classifier is encrypted with the IoT architecture to categories the online reading of the motor status and present it through an IoT dashboard as described in the following test scenarios. The flowchart in Fig. 14 describes the total operation of data acquisition, validation, and visualization.

Moreover, the procedure of the cyber-attack's detection based on the proposed IoT architecture with the machine learning technique is clarified in the following pseudo-code in Algorithm 1.



FIGURE 13. Receiver operating characteristic (ROC) curves of (a) DT classifier, (b) XGBoost classifier, and (c) RF classifier: where (0-normal, 1-inner ring fault, 2-outer ring fault, and 3-cyber-attack).

#### A. SCENARIO 1: NORMAL STATE

This scenario demonstrates the online monitoring for the bearing of the motor in the case of a normal state and



FIGURE 14. Flowchart of the proposed IoT topology with the various proposed machine learning classifiers.

stable network. Figure 15 presents the current status of the bearing and the reliability of the internet network on the dashboard of the CONTACT Elements for IoT. This figure shows that the motor status is normal which means the motor work well and the bearing does not have any fault. Furthermore, the light of the traffic indicator is green which means the system in a healthy state. Besides, Figure 15 shows that the internet network is stable, and the transmitted data is real. This test validates the reliability of the proposed IoT architecture and enhances the decision-making about the motor status.

#### B. SCENARIO 2: INNER RING FAULT

This scenario is created to confirm the capability of the proposed machine learning method and the IoT architecture to detect the inner ring fault in the bearing of the motor. Figure 16 shows the bearing status in the case of inner ring fault and stable network. The IoT dashboard clears that the bearing has an inner ring fault and the transmitted data via IoT is real. Besides, the traffic light changed to a yellow color that means the motor has a fault. This test affirms the ability of the proposed machine learning method and the IoT architecture to recognize the inner ring fault of the motor bearing without any error and clear visualization. Besides, the proposed



- 1: *Read* vibration signal from the motor microcontroller
- 2: Send signals to the IoT broker
- 3: Input signals to RF model
- 4: Classify the motor status by RF model
- 5: Connect to MQTT server
- **6:** if the output of RF model = 0
- 7: *Publish* that the motor status is 'Normal' and network status is 'Real data'.
- **8: else if** the output of RF model = 1
- **9:** *Publish* that the motor status is 'Inner ring fault' and network status is 'Real data'.
- **10: else if** the output of RF model = 2
- 11: *Publish* that the motor status is 'Outer ring fault' and network status is 'Real data'.
- **12: else if** the output of RF model = 3
- 13: *Publish* that the motor status is 'Fake data' and network status is 'Cyber-attacks'.
- 14: End



FIGURE 15. Motor status on the IoT dashboard in the case of the normal state.



FIGURE 16. Motor status on the IoT dashboard in the case of inner ring fault.

techniques check the transmitted data against any cyber-attacks that increase the reliability of the IoT topology.

# C. SCENARIO 3: OUTER RING FAULT

The outer ring fault of the motor bearing is created in this scenario to demonstrates the performance of the proposed machine learning method with IoT architecture to detect all fault classes in the motor bearing. Figure 17 presents the motor bearing and the network states in the case of the outer ring fault and safe data transmission. It is clear in the IoT dashboard that the proposed machine learning technique can recognize the motor fault of the outer ring. Furthermore, the traffic light changed from the green light of the normal



FIGURE 17. Motor status on the IoT dashboard in the case of outer ring fault.

CONTACT Elements for IoT				
A My Start Page	Digital Twin	067)		
Documents •	ID: DT000067 Name (en): Notor Category (en): Field Device Active: 1	Tenant: Responsible (en): Device ID: Motor	Item Num Batch Nun Serial Nun	ber (ERP): no information aber: no information aber: no information
Service Cases	Dashboard O Data Shee	et 🐴 Properties 🥥 Audit Trai	I 🛦 Activities 🍶 Diagrams	🗲 Events 🛛 Processes
>> Workflows	Red Red	Motor status	Networkstatus	
Organizations     Task Boards	Cyber-attacks     Cyber-attacks on the network	Fake data	Cyber-attacks	
🖌 Actions				

FIGURE 18. Network status on the IoT dashboard in the case of cyber-attacks detection.

state to the yellow light to inform the user about the abnormal state due to the outer ring fault of the motor bearing. Besides, the dashboard shows that the network is stable, and the transmitted data is real.

# D. SCENARIO 4: CYBER-ATTACKS DETECTION

Cyber-attacks are the main challenge against the implementation of the IoT system. So, this scenario is carried out to ensure the effectiveness of the proposed machine to recognize the cyber-attacks on the internet network. Figure 18 presents the transmitted data status in case of cyber-attacks on the internet network. It is clear from this figure that the proposed machine learning technique can detect cyber-attacks on internet networks and the proposed IoT architecture clears that the transmitted data about the motor status is fake data. Furthermore, the traffic light changed from the green light of the normal state to the red light to inform the user about the cyber-attacks on the network that enhance the decision-making to maintain and stabilize the internet network. This test confirms that the proposed machine learning with the IoT architecture can provide reliable monitoring for the motor status.

The results from the above scenarios can be concluded as follows;

- The proposed IoT architecture can visualize the normal status of the motor and the internet network status clearly on the dashboard of the IoT platform as presented in scenario 1 effectively without any errors.
- The inner ring fault of the motor can be detected effectively by the proposed IoT topology based on the machine learning technique as cleared in scenario 2. In addition, the suggested IoT platform performs an alarm and converted the color of the traffic light from

CONTACT Elements for IoT					
☆ My Start Page	nfluxDB Provider				
Documents					
Activities	O Data Sheet 👯 Data X Attributes				
💪 Digital Twins 🕠	Date				
A Service Cases 🔹 🔸	YYYY-MM-UD HH:mm:ss.555				
>> Workflows	End: VVV/MM-DD HH'mm'ss SSS A Search Reset				
🕑 Tasks					
Organizations	Drag Column Headers Here to Group				
	Time	Motor status	Network status		
III Task Boards	2021-03-05 14:32:11.075	Inner ring fault	Real data		
<b>6</b>	2021-03-05 14:32:13.147	Fake data	Cyber-attacks		
Actions	2021-03-05 14:32:15.234	Inner ring fault	Real data		
	2021-03-05 14:32:17.280	Inner ring fault	Real data		
	2021-03-05 14:32:19.325	Outer ring fault	Real data		
	2021-03-05 14:32:21.380	Normal	Real data		
	2021-03-05 14:32:23.430	Normal	Real data		
	2021-03-05 14:32:25.493	Normal	Real data		
	2021-03-05 14:32:27.568	Outer ring fault	Real data		
	2021-03-05 14:32:29.631	Inner ring fault	Real data		
	2021-03-05 14:32:32.352	Outer ring fault	Real data		
	2021-03-05 14:32:33.763	Normal	Real data		
	2021-03-05 14:32:35.832	Outer ring fault	Real data		
	2021-03-05 14:32:37.881	Fake data	Cyber-attacks		
	2021-03-05 14:32:39.947	Fake data	Cyber-attacks		

FIGURE 19. The latency/overhead of the proposed fault and cyberattack detection process based on the proposed IoT platform.

the green color to the yellow color to remind the user about the inner ring fault of the motor.

- The third test case shows the outer ring fault of the motor and emphases the superiority of the suggested IoT architecture based on the machine learning technique to recognize and visualize the outer ring fault of the motor effectively.
- The final scenario clears the superiority of the introduced machine learning technique to recognize the cyber-attacks on the network. Furthermore, the suggested IoT platform presents the status of transmitted data through the internet network if it is real or fake to enhance the decision-making about the motor status. Besides, the IoT platform converted the traffic light to red color in order to remind the user to take care of the network against cyber-attacks issue.
- The latency/overhead of the proposed fault and cyberattack detection process is analyzed by the proposed IoT platform and presented in Fig. 19.

# **V. CONCLUSION**

This paper introduces a new IoT architecture for online monitoring of the faults of the induction motor instead of the traditional methods. The proposed IoT architecture is developed based on effective machine learning techniques to recognize the fault classes of the motor. Besides, the cyber-attacks issue is taken into the account and the attack can be detected and suppressed by the proposed IoT topology. Different experimental testing is performed to confirm the effectiveness of the proposed IoT architecture based on machine learning. The results emphases the superiority of the prosed IoT architecture to recognize motor faults and cyber-attacks with high accuracy. Furthermore, the results are visualized on CONTACT Elements for IoT platform clearly that enhance the decision making about the motor statues. That allows the system to run for a long time in healthy conditions and improve the industrial environment that represents the main target of Industry 4.0. In addition, the proposed IoT architecture provides a promising solution to apply to different machines for future work.

#### ACKNOWLEDGMENT

This work was financially supported in part by the Department of Electrical Engineering and Automation, Aalto University, Espoo, Finland, and in part by The Ministry of Science and Technology (MOST) of Taiwan (grant numbers: MOST 110- 2222-E-011 -013- and MOST 110-2222-E-011-002-) and the "Center for Cyber-physical System Innovation" from the Featured Areas Research Center Program within the framework of the Higher Education Sprout Project by the Ministry of Education (MOE) in Taiwan. Moreover, the authors acknowledge the CONTACT Elements for IoT platform for supporting this work that applied in online monitoring of fault diagnosis in induction motors.

#### REFERENCES

- A. Singh, B. Grant, R. DeFour, C. Sharma, and S. Bahadoorsingh, "A review of induction motor fault modeling," *Electr. Power Syst. Res.*, vol. 133, pp. 191–197, Apr. 2016.
- [2] Y. Liu and A. M. Bazzi, "A review and comparison of fault detection and diagnosis methods for squirrel-cage induction motors: State of the art," *ISA Trans.*, vol. 70, pp. 400–409, Sep. 2017.
- [3] A. Choudhary, D. Goyal, S. L. Shimi, and A. Akula, "Condition monitoring and fault diagnosis of induction motors: A review," *Arch. Comput. Methods Eng.*, vol. 26, no. 4, pp. 1221–1238, Sep. 2019, doi: 10.1007/s11831-018-9286-z.
- [4] M. Blodt, P. Granjon, B. Raison, and J. Regnier, Mechanical Fault Detection in Induction Motor Drives Through Stator Current Monitoring— Theory and Application Examples. Rijeka, Croatia: InTech, 2010, pp. 451–488, doi: 10.5772/9072.

- [5] F. Cipollini, L. Oneto, A. Coraddu, and S. Savio, "Unsupervised deep learning for induction motor bearings monitoring," *Data-Enabled Discov*ery Appl., vol. 3, no. 1, p. 1, Dec. 2019.
- [6] F. Immovilli, C. Bianchini, M. Cocconcelli, A. Bellini, and R. Rubini, "Bearing fault model for induction motor with externally induced vibration," *IEEE Trans. Ind. Electron.*, vol. 60, no. 8, pp. 3408–3418, Aug. 2013.
- [7] J. J. Saucedo-Dorantes, M. Delgado-Prieto, J. A. Ortega-Redondo, R. A. Osornio-Rios, and R. D. J. Romero-Troncoso, "Multiple-fault detection methodology based on vibration and current analysis applied to bearings in induction motors and gearboxes on the kinematic chain," *Shock Vib.*, vol. 2016, Mar. 2016, Art. no. 5467643.
- [8] M. Iorgulescu and R. Beloiu, "Vibration and current monitoring for fault's diagnosis of induction motors," Elect. Eng. Ser., Ann. Univ. Craiova, Romania, Tech. Rep. 32, 2008, pp. 102–107.
- [9] M.-K. Liu, M.-Q. Tran, and P.-Y. Weng, "Fusion of vibration and current signatures for the fault diagnosis of induction machines," *Shock Vib.*, vol. 2019, Sep. 2019, Art. no. 7176482.
- [10] American Association for the Advancement of Science, "International standard time," *Science*, vol. 1, no. 6, pp. 159–160, Mar. 1883. [Online]. Available: https://www.jstor.org/stable/1758430
- [11] M. D. Prieto, G. Cirrincione, A. G. Espinosa, J. A. Ortega, and H. Henao, "Bearing fault detection by a novel condition-monitoring scheme based on statistical-time features and neural networks," *IEEE Trans. Ind. Electron.*, vol. 60, no. 8, pp. 3398–3407, Aug. 2013.
- [12] D. Wu, J. Wang, H. Wang, H. Liu, L. Lai, T. He, and T. Xie, "An automatic bearing fault diagnosis method based on characteristics frequency ratio," *Sensors*, vol. 20, no. 5, p. 1519, Mar. 2020.
- [13] P. Singh and S. Harsha, "Statistical and frequency analysis of vibrations signals of roller bearings using empirical mode decomposition," *Proc. Inst. Mech. Eng., K, J. Multi-Body Dyn.*, vol. 233, no. 4, pp. 856–870, Dec. 2019.
- [14] H.-C. Lin and Y.-C. Ye, "Reviews of bearing vibration measurement using fast Fourier transform and enhanced fast Fourier transform algorithms," *Adv. Mech. Eng.*, vol. 11, no. 1, pp. 1–12, 2019.
- [15] Q. Hu, Z. He, Z. Zhang, and Y. Zi, "Fault diagnosis of rotating machinery based on improved wavelet package transform and SVMs ensemble," *Mech. Syst. Signal Process.*, vol. 21, no. 2, pp. 688–705, Feb. 2007.
- [16] Z. K. Peng, F. L. Chu, and P. W. Tse, "Singularity analysis of the vibration signals by means of wavelet modulus maximal method," *Mech. Syst. Signal Process.*, vol. 21, no. 2, pp. 780–794, 2007.
- [17] Z. German-Sallo and H. S. Grif, "Hilbert–Huang transform in fault detection," *Proceedia Manuf.*, vol. 32, pp. 591–595, Jan. 2019.
- [18] P. K. Kankar, S. C. Sharma, and S. P. Harsha, "Rolling element bearing fault diagnosis using wavelet transform," *Neurocomputing*, vol. 74, no. 10, pp. 1638–1645, May 2011.
- [19] M.-K. Liu and P.-Y. Weng, "Fault diagnosis of ball bearing elements: A generic procedure based on time-frequency analysis," *Meas. Sci. Rev.*, vol. 19, no. 4, pp. 185–194, Aug. 2019.
- [20] I. Cruz-Vega, J. Rangel-Magdaleno, J. Ramirez-Cortes, and H. Peregrina-Barreto, "Automatic progressive damage detection of rotor bar in induction motor using vibration analysis and multiple classifiers," J. Mech. Sci. Technol., vol. 31, no. 6, pp. 2651–2662, Jun. 2017.
- [21] B.-S. Yang, X. Di, and T. Han, "Random forests classifier for machine fault diagnosis," *J. Mech. Sci. Technol.*, vol. 22, no. 9, pp. 1716–1725, Sep. 2008.
- [22] J. Xie, Z. Li, Z. Zhou, and S. Liu, "A novel bearing fault classification method based on XGBoost: The fusion of deep learning-based features and empirical features," *IEEE Trans. Instrum. Meas.*, vol. 70, pp. 1–9, 2021.
- [23] R. N. Toma and J.-M. Kim, "Bearing fault classification of induction motors using discrete wavelet transform and ensemble machine learning algorithms," *Appl. Sci.*, vol. 10, no. 15, p. 5251, Jul. 2020.
- [24] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner, "Gradient-based learning applied to document recognition," *Proc. IEEE*, vol. 86, no. 11, pp. 2278–2324, Nov. 1998.
- [25] Y. Ma, X. Jia, H. Bai, G. Liu, G. Wang, C. Guo, and S. Wang, "A new fault diagnosis method based on convolutional neural network and compressive sensing," J. Mech. Sci. Technol., vol. 33, no. 11, pp. 5177–5188, Nov. 2019.
- [26] O. Janssens, V. Slavkovikj, B. Vervisch, K. Stockman, M. Loccufier, S. Verstockt, R. Van de Walle, and S. Van Hoecke, "Convolutional neural network based fault detection for rotating machinery," *J. Sound Vib.*, vol. 377, pp. 331–345, Sep. 2016.

- [27] L. Xiao, Y. Li, X. Huang, and X. Du, "Cloud-based malware detection game for mobile devices with offloading," *IEEE. Trans. Mobile Comput.*, vol. 16, no. 10, pp. 2742–2750, Oct. 2017, doi: 10.1109/TMC.2017.2687918.
- [28] F. Civerchia, S. Bocchino, C. Salvadori, E. Rossi, L. Maggiani, and M. Petracca, "Industrial Internet of Things monitoring solution for advanced predictive maintenance applications," *J. Ind. Inf. Integr.*, vol. 7, pp. 4–12, Sep. 2017.
- [29] R. Y. Zhong, L. Wang, and X. Xu, "An IoT-enabled real-time machine status monitoring approach for cloud manufacturing," *Procedia CIRP*, vol. 63, pp. 709–714, Jul. 2017.
- [30] Q. Cao, F. Giustozzi, C. Zanni-Merk, F. de Bertrand de Beuvron, and C. Reich, "Smart condition monitoring for industry 4.0 manufacturing processes: An ontology-based approach," *Cybern. Syst.*, vol. 50, no. 2, pp. 82–96, Feb. 2019.
- [31] R. Y. Zhong, X. Xu, E. Klotz, and S. T. Newman, "Intelligent manufacturing in the context of industry 4.0: A review," *Engineering*, vol. 3, no. 5, pp. 616–630, Jan. 2017.
- [32] S. Phuyal, D. Bista, and R. Bista, "Challenges, opportunities and future directions of smart manufacturing: A state of art review," *Sustain. Futures*, vol. 2, Jan. 2020, Art. no. 100023.
- [33] (Dec. 22, 2020). IoT Platform for Digital Business Models | CONTACT Software. [Online]. Available: https://www.contact-software. com/en/products/iot-platform-for-digital-business-models/?fbclid =IwAR0oYDd4qHpCd0BEZaGrLHEAQGYoQ2BhBmDzbF35cyM6QrNHAkziWDC8yo
- [34] M. Elsisi, M.-Q. Tran, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "Deep learning-based industry 4.0 and Internet of Things towards effective energy management for smart buildings," *Sensors*, vol. 21, no. 4, p. 1038, Feb. 2021.
- [35] M. Elsisi, M.-Q. Tran, K. Mahmoud, D.-E.-A. Mansour, M. Lehtonen, and M. M. F. Darwish, "Towards secured online monitoring for digitalized GIS against cyber-attacks based on IoT and machine learning," *IEEE Access*, vol. 9, pp. 78415–78427, 2021, doi: 10.1109/ACCESS.2021.3083499.
- [36] M. Elsisi, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "Reliable industry 4.0 based on machine learning and IoT for analyzing, monitoring, and securing smart meters," *Sensors*, vol. 21, no. 2, p. 487, Jan. 2021.
- [37] M. Elsisi, M.-Q. Tran, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "Robust design of ANFIS-based blade pitch controller for wind energy conversion systems against wind speed fluctuations," *IEEE Access*, vol. 9, pp. 37894–37904, 2021, doi: 10.1109/ACCESS.2021.3063053.
- [38] J. G. Ferreira and A. Warzecha, "An application of machine learning approach to fault detection of a synchronous machine," in *Proc. Int. Symp. Electr. Mach. (SME)*, Jun. 2017, pp. 1–6.
- [39] M. N. Ali, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "An efficient fuzzy-logic based variable-step incremental conductance MPPT method for grid-connected PV systems," *IEEE Access*, vol. 9, pp. 26420–26430, 2021, doi: 10.1109/ACCESS.2021.3058052.
- [40] M. Elsisi, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "An improved neural network algorithm to efficiently track various trajectories of robot manipulator arms," *IEEE Access*, vol. 9, pp. 11911–11920, 2021, doi: 10.1109/ACCESS.2021.3051807.
- [41] M. Elsisi, K. Mahmoud, M. Lehtonen, and M. M. F. Darwish, "Effective nonlinear model predictive control scheme tuned by improved NN for robotic manipulators," *IEEE Access*, vol. 9, pp. 64278–64290, 2021, doi: 10.1109/ACCESS.2021.3075581.
- [42] D. Zhang, L. Qian, B. Mao, C. Huang, B. Huang, and Y. Si, "A data-driven design for fault detection of wind turbines using random forests and XGboost," *IEEE Access*, vol. 6, pp. 21020–21031, 2018.
- [43] Y. Zhao, L. Yang, B. Lehman, J.-F. de Palma, J. Mosesian, and R. Lyons, "Decision tree-based fault detection and classification in solar photovoltaic arrays," in *Proc. 27th Annu. IEEE Appl. Power Electron. Conf. Expo.* (APEC), Feb. 2012, pp. 93–99.
- [44] R. Benkercha and S. Moulahoum, "Fault detection and diagnosis based on C4.5 decision tree algorithm for grid connected PV system," *Sol. Energy*, vol. 173, pp. 610–634, Oct. 2018.
- [45] C. Aldrich and L. Auret, "Fault detection and diagnosis with random forest feature extraction and variable importance methods," *IFAC Proc. Volumes*, vol. 43, no. 9, pp. 79–86, Jan. 2010.
- [46] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discovery Data Mining*, San Francisco, CA, USA, Aug. 2016, pp. 785–794, doi: 10.1145/2939672.2939785.

# **IEEE**Access

- [47] Z. Wu, X. Wang, and B. Jiang, "Fault diagnosis for wind turbines based on ReliefF and eXtreme gradient boosting," *Appl. Sci.*, vol. 10, no. 9, p. 3258, May 2020.
- [48] J. H. Friedman, "Greedy function approximation: A gradient boosting machine," Ann. Statist., vol. 29, no. 5, pp. 1189–1232, Oct. 2001.
- [49] T. Yu and H. Zhu, "Hyper-parameter optimization: A review of algorithms and applications," 2020, arXiv:2003.05689. [Online]. Available: http://arxiv.org/abs/2003.05689



**MENG-KUN LIU** received the Ph.D. degree in mechanical engineering from Texas A&M University, USA, in 2012. In 2014, he has joined the Department of Mechanical Engineering, National Taiwan University of Science and Technology, as an Associate Professor. His research interests include time-frequency analysis of manufacturing processes, sensorless fault diagnosis of induction motors, robot force control, and chaos control.



**MINH-QUANG TRAN** received the B.Sc. degree in mechanical engineering from Thai Nguyen University of Technology, Vietnam, in 2011, and the M.Sc. and Ph.D. degrees in mechanical engineering from the National Taiwan University of Science and Technology, Taiwan, in 2017 and 2020, respectively.

Since 2011, he worked as a Lecturer with the Department of Mechanical Engineering, Thai Nguyen University of Technology. He is currently

a Project Assistant Professor with the Industry 4.0 Implementation Center, Center for Cyber-Physical System Innovation, National Taiwan University of Science and Technology. His research interests include tool condition monitoring, machining dynamics, signal analysis of manufacturing process, machine learning, and intelligent systems for industry 4.0.



**MAHMOUD ELSISI** was born in Cairo, Egypt, in 1989. He received the B.Sc., M.Sc., and Ph.D. degrees from the Electrical Engineering Department, Faculty of Engineering at Shoubra, Benha University, Cairo, in 2011, 2014, and 2017, respectively.

Since 2017, he worked as an Assistant Professor at the Electrical Engineering Department, Faculty of Engineering at Shoubra, Benha University. He is currently a Postdoctoral Researcher with

the Industry 4.0 Implementation Center, Center for Cyber-Physical System Innovation, National Taiwan University of Science and Technology, Taiwan. His research interests include studying the power system dynamics: stability and control, artificial intelligence techniques, robotics, industry 4.0, the IoT, and applied machine learning.



**KARAR MAHMOUD** received the B.Sc. and M.Sc. degrees in electrical engineering from Aswan University, Aswan, Egypt, in 2008 and 2012, respectively, and the Ph.D. degree from the Electric Power and Energy System Laboratory (EPESL), Graduate School of Engineering, Hiroshima University, Hiroshima, Japan, in 2016.

Since 2010, he has been with Aswan University, where he is currently an Associate Professor with the Department of Electrical Engineering, Faculty

of Engineering, Aswan University. He is also a Postdoctoral Researcher with the Group of Prof. M. Lehtonen, School of Electrical Engineering, Aalto University, Finland. He has authored or coauthored several publications in top-ranked journals, including IEEE journals, international conferences, and book chapters. His research interests include power systems, renewable energies, smart grids, distributed generation, optimization, applied machine learning, the IoT, industry 4.0, and high voltage. Since 2021, he has also been a Topic Editor of *Sensors* journal (MDPI).



**MATTI LEHTONEN** received the master's and Licentiate degrees in electrical engineering from Helsinki University of Technology, Finland, in 1984 and 1989, respectively, and the Doctor of Technology degree from Tampere University of Technology, Finland, in 1992.

He was with VTT Energy, Espoo, Finland, from 1987 to 2003. He has been a Full Professor and the Head of the Power Systems and High Voltage Engineering Groups, Aalto University, Espoo,

Finland, since 1999. His research interests include power system planning and assets management, power system protection including earth fault problems, harmonic related issues, high voltage systems, power cable insulation, and polymer nanocomposites. He is an Associate Editor of *Electric Power Systems Research* and *IET Generation, Transmission & Distribution*.



**MOHAMED M. F. DARWISH** was born in Cairo, Egypt, in 1989. He received the B.Sc., M.Sc., and Ph.D. degrees in electrical engineering from the Faculty of Engineering at Shoubra, Benha University, Cairo, in May 2011, June 2014, and January 2018, respectively. From 2016 to 2017, he was with Aalto University, Finland, as a Ph.D. student with the Department of Electrical Engineering and Automation (EEA) and with Prof. M. Lehtonen's Group.

He is currently working as an Assistant Professor with the Department of Electrical Engineering, Faculty of Engineering at Shoubra, Benha University. He is also a Postdoctoral Researcher with the Department of EEA, School of Electrical Engineering, Aalto University. He has authored in several international IEEE journals and conferences. His research interests include HV polymer nanocomposites, nano-fluids, partial discharge detection, dissolved gas analysis, fault diagnosis, electromagnetic fields, renewables, optimization, applied machine learning, the IoT, industry 4.0, control systems, and superconducting materials. He received the Best Ph.D. Thesis Prize that serves industrial life and society all over the Benha University Staff for the academic year 2018 to 2019. Since 2021, he has been a Topic Editor of *Catalysts* journal (MDPI).